DOMINUS





ROBORIS 007AX13

S3 SRC EN ISO 20345:2011 36 to 47

> Low shoe **Urban sport**











- Low urban sport safety shoe, black colour. PU toe protection in front.
- Upper in water-resistant leather, grained finish, 1.9 / 2.1mm thick.
- 3D.LINING° in three-ply material for improved evacuation of moisture to the exterior, high breathability and fast-drying.
- Vamp lining in non-woven fabric. Resists abrasion and acid perspiration.
- Padded collar. Provides comfort to the ankle-bones and protects the Achilles tendon.
- Fastened by lacing through 5 pairs of perforations. Laces 90 cm 36 to 41 and 110 cm 42 to 47.
- Padded tongue to provide better protection to the instep, combined with two side gussets to prevent grit from entering the shoe.
- Soft footbed made of BASF Dynamic polyurethane with heat sensitive memory foam and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical and breathable.
- This is a DGUV 112-191 certified model, with the option of swapping the hygienic insole provided for a SECOSOL® orthopaedic insole.
- Stab-proof non-metallic FLEX-SYSTEM® liner: total protection of the sole of the foot.
- LIGHT-PLUS® protective toecap in synthetic material offering protection from an impact of 200 J.

Slip resistance tests results EN Standard : EN ISO 20345 : 2011 Requirement SRC (SRA+SRB)

SRA Test ground: ceramic / lubricant: water and detergent On flat **0,49** (>0,32) - On the heel **0,35** (>0,28)

SRB Test ground steel / lubricant : glycerine On flat **0,26** (>0,18) - On the heel: **0,18** (>0,13)

W-Tech Wrapping Technology sole in PU dual density:

- Resists oils and hydrocarbons.
- Slim, streamlined profile rising towards the toes.
- Absorption of heel impact > 20 joules
- Wrap-around profile for better stability when walking

Weight	Gross Weight (42): 1312 g / Net weight (42): 1094 g			
Size	38 to 39	40 to 41	42 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Dimensions (mm)	306 x 192 x 114		340 x 210 x 133	
Dimensions box (mm)	585 x 199 x 315	585 x 395 x 315	680 x 425 x 350	680 x 215 x 350

