

## NITRUS 007AX86

S3 SRC  
EN ISO 20345:2011

38 to 47

Low shoe  
Urban sport



SPÉCIFIQUE  
PÉTRO-CHIMIE

metal  
FREE

3DLining

WAT-OUT

Light  
PLUS

SOFT

FLEXsystem  
ZERO

W-TECH

- Low urban sport safety shoe, black colour. PU toe protection in front.
- Wat-Out microfiber upper with resin combines optimal breathability and unmatched watertightness.
- 3D.LINING**® in three-ply material for improved evacuation of moisture to the exterior, high breathability and fast-drying.
- Vamp lining in non-woven fabric. Resists abrasion and acid perspiration.
- Padded collar. Provides comfort to the ankle-bones and protects the Achilles tendon.
- Fastened by lacing through 4 pairs of lace stays. Laces 90 cm 36 to 41 and 110 cm 42 to 47.
- Padded tongue to provide better protection to the instep, combined with two side gussets to prevent grit from entering the shoe.
- Soft** footbed made of **BASF Dynamic polyurethane** with heat sensitive memory foam and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical and breathable.
- Stab-proof non-metallic **FLEX-SYSTEM**® liner : total protection of the sole of the foot.
- LIGHT-PLUS**® protective toecap in synthetic material offering protection from an impact of 200 J.

#### Slip resistance tests results

EN Standard : EN ISO 20345 : 2011 **Requirement SRC**  
(SRA+SRB)

**SRA** Test ground : ceramic / lubricant : water and detergent  
On flat **0,49** (>0,32) – On the heel **0,35** (>0,28)

**SRB** Test ground steel / lubricant : glycerine  
On flat **0,26** (>0,18) – On the heel: **0,18** (>0,13)

#### W-Tech Wrapping Technology sole in PU dual density :

- Resists oils and hydrocarbons .
- Slim, streamlined profile rising towards the toes.
- Absorption of heel impact > 20 joules
- Wrap-around profile for better stability when walking



Weight	Gross Weight (42) : 1300 g / Net weight (42) : 1082 g			
Size	38 to 39	40 to 41	42 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Dimensions (mm)	306 x 192 x 114		340 x 210 x 133	
Dimensions box (mm)	585 x 199 x 315	585 x 395 x 315	680 x 425 x 350	680 x 215 x 350