



NEPTUNE
7FR14

S1P SRC
EN ISO 20345:2011
37 to 47

Low shoe
Urban sport

FREE

Light **PLUS**

PLUS
VENTO

FLEX system
ZERO

metal
FREE

- Ⓜ Low urban sport safety shoe, blue colour. PU toe protection in front.
- Ⓜ Suede leather upper Thickness 1,9 / 2,1. Perforated for high breathability.
- Ⓜ Unlined.
- Ⓜ Vamp lining in non-woven fabric. Resists abrasion and acid perspiration.
- Ⓜ Padded collar. Provides comfort to the ankle-bones and protects the Achilles tendon.
- Ⓜ Fastened by lacing. Laces 100 cm.
- Ⓜ Padded tongue to provide better protection to the instep, combined with two side gussets to prevent grit from entering the shoe.
- Ⓜ Complete **VENTO-PLUS**® anatomical and antistatic inlay, with honeycomb structure for improved air circulation.
- Ⓜ Stab-proof non-metallic **FLEX-SYSTEM**® liner : total protection of the sole of the foot.
- Ⓜ **LIGHT-PLUS**® protective toecap in synthetic material offering protection from an impact of 200 J.

Slip resistance tests results

EN Standard : EN ISO 20345 : 2011

Requirement SRC (SRA+SRB)

SRA Test ground : ceramic / lubricant : water and detergent

On flat **0,70** (>0,32) – On the heel **0,48** (>0,28)

SRB Test ground steel / lubricant : glycerine

On flat **0,23** (>0,18) – On the heel: **0,19** (>0,13)

Sole FREE in PU dual density :

- Resists oils and hydrocarbons .
- Innovative design, linear profile.
- Absorption of heel impact > 20 joules
- Wrap-around profile for better stability when walking

| | | | | |
|-----------------|---|-----------------|-----------------|-----------------|
| Weight | Gross Weight (42) : 1390 g / Net Weight (42) : 1182 g | | | |
| Size | 37 to 39 | 40 to 41 | 42 to 45 | 46 to 47 |
| Packaging | 5 pairs | 10 pairs | | 5 pairs |
| Box (mm) | 306 x 192 x 114 | | 340 x 210 x 133 | |
| Dimensions (mm) | 585 x 199 x 315 | 585 x 395 x 315 | 680 x 425 x 350 | 680 x 215 x 350 |

