



BALI ESD
7X102

S1P SRC
EN ISO 20345:2011
38 to 47

Low shoe



DOMINUS



- ⊗ Low safety shoe, sandals type, protecting the electronic devices against electrostatic discharge phenomena. Electrostatic dissipative shoes ESD Environmental Class II tested according to EN 61340-4-3 and EN 61340-5-1. PU toe protection in front. Color black and red.
- ⊗ Leather upper pull-up finished. Thickness 1,9 / 2,1. Perforated for better foot ventilation.
- ⊗ **3D.LINING**® in three-ply material for improved evacuation of moisture to the exterior, high breathability and fast-drying.
- ⊗ Vamp lining in non-woven fabric. Resists abrasion and acid perspiration.
- ⊗ Padded collar. Provides comfort to the ankle-bones and protects the Achilles tendon.
- ⊗ Rapid closure system with two velcro bands.
- ⊗ Padded tongue to provide better protection to the instep.
- ⊗ Complete **COMFORT PLUS**® inlay, antistatic and anatomically shaped in flexible polyurethane covered in breathable, absorbent fabric.
- ⊗ This is a **DGUV 112-191** certified model, with the option of swapping the hygienic insole provided for a **SECOSOL**® ESD orthopaedic insole.
- ⊗ Stab-proof non-metallic **FLEX-SYSTEM**® liner : total protection of the sole of the foot.
- ⊗ **LIGHT-PLUS**® protective toecap in synthetic material offering protection from an impact of 200 J.



Slip resistance tests results	
EN Standard : EN ISO 20345 : 2011	
Requirement SRC (SRA+SRB)	
SRA Test ground : ceramic / lubricant : water and detergent	
On flat 0,44 (>0,32) – On the heel 0,37 (>0,28)	
SRB Test ground steel / lubricant : glycerine	
On flat 0,19 (>0,18) – On the heel: 0,15 (>0,13)	

W-Tech Wrapping Technology sole in PU dual density :

- Resists oils and hydrocarbons .
- Slim, streamlined profile rising towards the toes.
- Absorption of heel impact > 20 joules
- Wrap-around profile for better stability when walking



Weight	Gross Weight (42) : 1312 g / Net weight (42) : 1094 g			
Size	38 to 39	40 to 41	42 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Dimensions (mm)	306 x 192 x 114		340 x 210 x 133	
Dimensions box (mm)	585 x 199 x 315	585 x 395 x 315	680 x 425 x 350	680 x 215 x 350