



**S2 SRC**  
**EN ISO 20345:2011**  
**35 to 48**

**Sporty urban safety shoes**  
**Antistatic**



**OVERDRY**

**SOFT**

**ALULITE**

**FLEXsystem**  
ZERO

- White sporty urban safety shoes .
- Water resistant microfiber upper. Washable in soap and water.
- Upper lined in technical textiles OVER DRY, very resistant and high breathability.
- Vamp lined in non-woven fabric.
- Padded collar with compact flexible foam for extra comfort and better ankle and Achilles tendon protection.
- Snug fit thanks to elastic band underneath protective tongue.
- **Soft** footbed made of **BASF Dynamic polyurethane** with heat sensitive memory foam and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical and breathable.
- This is a **DGUV 112-191** certified model, with the option of swapping the hygienic insole
- provided for a **SECOSOL®** orthopaedic insole.
- **FLEX-SYSTEM®** Stab-resistant structural insole and liner antistatic and 100% composite in compliance with standard 12568:2010.
- **ALU-LITE®** 200 J aluminium safety toe cap, anti corrosion and 50% lighter than steel material.



**Dual density PU sole** , outsole in PU white.

- ▶ Out-sole design featuring specific transversal grooves, high performance of slip resistance.
- ▶ Resistant to oils and hydrocarbons.
- ▶ Sporty profile and design.
- ▶ Heel shock absorption > 20 Joules.

**Slip resistance tests results**

EN Standard : EN ISO 20345 : 2011

**Requirement SRC (SRA+SRB)**

**SRA** Test ground : ceramic / lubricant :  
water and detergent

On flat **0,98** (>0,32) – On the heel **0,74**  
(>0,28)

**SRB** Test ground steel / lubricant : glycerine

On flat **0,40** (>0,18) – On the heel: **0,35**  
(>0,13)

Weight	Gross Weight (42) : 1282 g / Net Weight (42) : 1074 g			
Size	35 to 39	40 to 41	42 to 45	46 to 48
Packaging	5 pairs		10 pairs	
Box (mm)	306 x 192 x 114		340 x 210 x 133	
Dimensions (mm)	585 x 199 x 315	585 x 395 x 315	680 x 425 x 350	680 x 215 x 350