



**ANGEL  
ATR02**

**S3 SRC  
EN ISO 20345:2011  
35 to 48**

**High shoe  
Trekking style**



## TEAM RESCUE



- High safety shoe, trekking, type, black / yellow color.
- Water-repellent full-grain leather upper. Inserts in water-repellent technical textiles. Pu reinforcement to the front of the sole to reinforce the boot and prolong its life.
- 3D.LINING**® in three-ply material for improved evacuation of moisture to the exterior, high breathability and fast-drying.
- Vamp lining in non-woven fabric. Resists abrasion and acid perspiration.
- Reflective piping on quarters, ideal for night work.
- Ergonomic padded collar with compact flexible foam for extra comfort and better ankle and Achilles tendon protection.
- Padded and lined leather tongue for instep protection with side bellows to keep out dust and dirt.
- Lace up on five pairs of lace stays . Laces 120 cm.
- Complete **COMFORT PLUS**® inlay, antistatic and anatomically shaped in flexible polyurethane covered in breathable, absorbent fabric.
- This is a **DGUV 112-191** certified model, with the option of swapping the hygienic insole provided for a **SECOSOL**® orthopaedic insole.
- Stab-proof non-metallic **FLEX-SYSTEM**® **zéro** liner : total protection of the sole of the foot.
- LIGHT-PLUS**® protective toecap in synthetic material offering protection from an impact of 200 J.
- Antistatic shoe



**Slip resistance EN ISO 20345:2011  
Qualité SRC (SRA+SRB)**

**SRA** Test ground/Ceramic/lubricant  
Water and detergent

On flat **0,38** (>0,32) - On the heel **0,31** (>0,28)

**SRB** Test ground : steel/lubricant  
Glycerine

On flat **0,20** (>0,18)- On the heel **0,17** (>0,13)

**Sole** in PU dual density :

- Resists oils and hydrocarbons .
- Wrap-around profile for better stability when walking.
- Absorption of heel impact > 20 joules.
- Maximum comfort.



Weight	Gross weight (42) : 1428 g / Net weight (42) : 1220 g			
Size	35 to 39	40 to 41	42 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Box (mm)	306 x 192 x 114		340 x 210 x 133	
Dimensions (mm)	585 x 199 x 315	585 x 395 x 315	680 x 425 x 350	680 x 215 x 350