## **JALBIO V** 00J0271







S2 HRO SRC EN ISO 20345: 2011 35 to 47





- Aseptane™ upper
- Triftane™ sole
  - Loafer shoes ideal for food industry jobs.
  - ❖ White Aseptane™ upper with microfiber resin combines optimal breathability and unmatched watertightness.
  - Resistant to greasy and aggressive spilled and splashed liquids. Minimal stitching for improved hygiene and easy upkeep. Washable in soap and water.
  - Snug fit thanks to elastic band underneath protective tongue.
  - Vamp lining in non-woven fabric. Resists scuffing and acid perspiration.
  - Stiffener reinforces the heel seat.
  - Inlay covering the entire surface of the foot, removable, antistatic, treated against bacteria, anatomical and with heel cushioning. High capacity for absorbing and evaporating perspiration.
  - 200 Joules safety toe cap is perforated for extra air flow around the toes.
  - ◆ TRIFTANE™ VIBRAM sole technology with a high adherence coefficient. Versatility of use. New formulation for increased durability.

## Slip resistance tests results EN Standard: EN ISO 20345: 2022

Tiled floor / Water and detergent From heel to toe **0,63** (>0,31) From the forefoot to the back 0,58 (>0,36)

Tiled floor / Glycerine From heel to toe **0,34** (>0,19) From the forefoot to the back **0,27** (>0,22)

- Better mechanical resistance to abrasion, peeling and tearing.
- NBR shore hardness: 60
- Optimum grip level.
- Hyperfunctional studs.
- Heel shock absorbtion 28 Joules
- Hollow heel, the hollowed out centre area makes wearers feel lighter as the y walk.
- Softane™ comfort layer, density 0.45
- Resistant to oils and hydrocarbons, and acids and bases at low concentrations.
- Resistant to direct contact heat up to 300°C.

Weight	Gross weight (42): 1160 g / Net weight (42): 890 g			
Size	35 to 39	40 to 42	43 to 45	46 to 47
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	342 x 213 x 114		350 x 245 x 133	
Cartons (mm)	590 x 220 x 348	590 x 437 x 348	685 x 500 x 355	685 x 250 x 358



