

# LIGHTANE™

## JALCORDEE X2 J0339

S1 P HRO SRC  
EN ISO 20345:2011  
39 to 47



- Suede
- Softane™/Néotril Lightane™ sole

- ❖ Low safety shoe, hiking type. Colour grey.
- ❖ Upper in perforated butt suede, thickness 1.9 / 2.1 mm.
- ❖ 3D™ textile inner lining of the quarters and bellows tongue, combining foam for comfort and protection and an open structure (mesh panel) that improves air flow around the foot.
- ❖ Padded ergonomic collar in compact flexible foam, lined for extra comfort and better ankle and Achilles tendon protection.
- ❖ Padded tongue to protect the top of the foot. Side bellows to keep out dust and dirt.
- ❖ Lace up on 4 pairs of non-metallic lace stays. Black and grey laces : 100 cm.
- ❖ Vamp lined in leather.
- ❖ Back tab makes them easy to pull on.
- ❖ Counter to maintain a snug-fitting heel.
- ❖ POLYJAL footbed single-block structure made of soft polyurethane and textile, anatomical, perforated in the front part and with heel shock absorbers.
- ❖ 100% composite safety: 200 Joules, Xetane™ safety toecap
- ❖ New manufacturing process: Stab-resistant structural insole and liner in FleXtane™ By Jallatte, in compliance with standard 12568:2010, antistatic, 100% composite. Sewn directly onto the upper and covering 100% of the foot for total protection. 100% composite materials: lighter than steel, non-magnetic, do not conduct heat or cold.

### Outsole in dual component Lightane™ :

➤ Softane™ comfort layer  
Density = 0.40. Ensures wearer comfort. Helps absorb vibrations and ensures thermal insulation for bottom of feet.

- Ground contact layer in rubber / Neotril with built-in "3A" concept :
  - Progressive shock absorber (36 Joules) cushions impacts and protects the back and joints against vibrations.
  - Antitorsion system optimises underfoot stability
  - Grip in compliance with ISO 20345:2011 standard. Deep, self-cleaning, flared treads improve grip in difficult wearing conditions such as unstable and oily surfaces.
  - Highly resistant to oils, hydrocarbons, greases and contact heat (300°C).
  - Highly resistant to abrasion

#### Slip resistance tests results

EN Standard : EN ISO 20345 : 2011  
Requirement SRC (SRA+SRB)

SRA Test ground : ceramic / lubricant :  
water and detergent  
On flat 0,40 (>0,32) – On the heel 0,42  
(>0,28)

SRB Test ground steel / lubricant : glycerine  
On flat 0,32 (>0,18) – On the heel: 0,23  
(>0,13)

Weight	Gross weight (42): 1258 g / Net weight (42): 1040 g			
Size	39	40 to 42	43 to 45	46 to 47
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	342 x 213 x 114		350 x 245 x 133	
Cartons (mm)	590 x 220 x 348	590 x 437 x 348	685 x 500 x 355	685 x 250 x 358



www.jallatte.com