

S3 SRC
EN ISO 20345:2011
38 to 47



- **Full grain leather**
- **J-Smarter PU single-density sole**
- **Steel toe cap B / Midsole no metallic**
- **Antistatic**

- ❖ Black safety shoe, derby type. Straight toe-cap.
- ❖ Classic and elegant design.
- ❖ Water-repellent full-grain leather upper, 1,5/ 1,7 mm thick.
- ❖ Leather lining quarter.
- ❖ Lined full grain leather tongue.
- ❖ Vamp lined in non-woven fabric. Resists scuffing and acid perspiration.
- ❖ Fastens with black laces : 75 cm.
- ❖ **J-confort**, anatomic footbed in soft micro-channelled material, lined with breathable and abrasion-resistant Vita- Plus fabric.. Antistatic.
- ❖ Heel stiffener to reinforce the heel seat.
- ❖ Stab-resistant **FleXtane™** insole and liner by Jallatte, antistatic, 100 % composite. Sewn directly onto the upper and covering 100 % of the foot for total protection.
- ❖ 200 Joules steel toe-cap

Slip resistance tests results

EN Standard : EN ISO 20345 : 2011

Requirement SRC (SRA+SRB)

SRA Test ground : ceramic / lubricant : water and detergent

On flat **0,34** (>0,32) – On the heel **0,29** (>0,28)

SRB Test ground steel / lubricant : glycerine

On flat **0,19** (>0,18) – On the heel: **0,15** (>0,13)

Single density polyuréthane sole :

- Highly resistant to oils and hydrocarbons
- The pattern design is purposed made to enhance comfort while waling and standing.
- Abrasion resistant.
- Heel-shock absorption > 20 Joules.



Weight	Gross weight (42) : 1218 g / Net weight (42) : 1000 g			
Size	38 to 39	40	41 to 45	46 to 47
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	306 x 192 x 114		340 x 210 x 133	
Cartons (mm)	590 x 210 x 320	590 x 410 x 320	685 x 440 x 359	685 x 225 x 359