

# TRIFTANE™ Fighter

## JALFOXBAT X2 JJ707

S3 CI HRO SRC  
EN ISO 20345:2011  
35 to 47



- **Water-repellent full grain leather**
- **TRIFTANE™ Fighter sole**

- ❖ Black urban sport shoe assuring better stability during walking thanks to the TPU heel reinforcement.
- ❖ Water-repellent full grain upper, pull-up finish, 1,9 / 2,1 mm thick.
- ❖ Breathable upper lining in 3D mesh, with honeycomb structure for improved all-round ventilation of the foot and fast-drying.
- ❖ Padded ergonomic collar in compact flexible foam, lined for extra comfort and better ankle and Achilles tendon protection.
- ❖ Padded tongue for good instep protection, combined with two side bellows to prevent any dirt from getting into the boots.
- ❖ Lace up on five pairs of non-metallic eyelets. Laces : 110 cm .
- ❖ Heel stiffener to reinforce the heel seat.
- ❖ J-Multitech footbed : single-block structure made of soft polyurethane and designed to support the foot movement for maximum comfort and energy absorption, especially in the heel area. Perforated in the front part for improved ventilation.
- ❖ **Xetane™** 200 Joule toe-cap, **100% composite** fibre. Non-magnetic, lightweight.
- ❖ **FleXtane™** By Jallatte anti-perforation inner sole and insert 100 % composite, yielding and flexible, non-detectable, non-magnetic and 70 % lighter than steel. Directly sewn to the bootstrap for 100% protection of the whole surface of the foot.
- ❖ 100% composite materials: lighter than steel, amagnetic, non-conductive of heat and cold.
- **Triftane™ Fighter sole** : innovative multifunctional outsole, made of 3 different parts, with a high slip resistant coefficient :

- The Oxytane comfort layer increases the softness, flexibility and the cushioning capacity thanks to its specific density and high concentration of closed cells which absorb heel shocks and vibrations.
- The NBR outsole (Nitrile Butadiene rubber) keeps from fatigue and improves adherence. The innovative position of the sole pattern follows the foot's natural motion for better grip on any surface, besides preventing dirt and liquid from lying under the soke.
- The NBR protective grid reinforces the entire structure and improves the shoe's durability, contact heat resistant to 300° C.

### Slip resistance tests results

EN Standard : EN ISO 20345 : 2011

#### Requirement SRC (SRA+SRB)

**SRA** Test ground : ceramic / lubricant : water and detergent

On flat **0,50** (>0,32) – On the heel **0,48** (>0,28)

**SRB** Test ground steel/lubricant : glycerine

On flat **0,35** (>0,18) – On the heel: **0,25** (>0,13)

Weight	Gross weight (42): 1390 g / Net weight (42): 1172 g			
Size	35 to 39	40 to 42	43 to 45	46 to 47
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	342 x 213 x 114		350 x 245 x 133	
Cartons (mm)	590 x 220 x 348	590 x 437 x 348	685 x 500 x 355	685 x 250 x 358



www.jallatte.com