

ELENA JJD23

S3 SRC
EN ISO 20345:2011
35 to 42

- **Aseptane™** upper
- **J-DREAM** dual-density TPU sole



- ❖ **Aseptane™** upper : Microfibre resistant to fluid projection, it is ideal for wet working conditions. Water-repellent, breathable, washable at 30° C.
 - ❖ Anti-bacterial nylon lining.
 - ❖ Vamp lining in non-woven fabric. Resists scuffing and acid perspiration.
 - ❖ Padded collar for extra comfort and better ankle and Achilles tendon protection.
 - ❖ Closure by black laces (90 cm). Padded textile tongue for good instep protection, combined with two side bellows to prevent any dirt from getting into the boots.
 - ❖ Heel stiffener to reinforce the heel seat.
 - ❖ **J-Souplesse** footbed : full piece, antistatic and anatomic, in soft polyurethane covered with a special fiber; perforated in the front part for better foot venting, cushioning effect in the heel area.
 - ❖ Antiperforation insert : **FleXtane™** Zero millimeter, made of textile composite materials, it protects 100 % of the support surface of the foot and it can't be detected by metal detectors. EN ISO 12568:2010 approved.
 - ❖ 200 Joules steel toe cap with perforations.
- **J-Dream dual density TPU sole, sporty profile :**

Slip resistance tests results

EN Standard : EN ISO 20345 : 2011

Requirement SRC (SRA+SRB)

SRA Test ground : ceramic / lubricant : water and detergent

On flat **0,40** (>0,32) – On the heel **0,39** (>0,28)

SRB Test ground steel / lubricant : glycerine

On flat **0,19** (>0,18) – On the heel: **0,16** (>0,13)

- ✓ Abrasion resistance.
- ✓ Highly resistant to oils and hydrocarbons.
- ✓ Heel shock absorption 20 Joules.
- ✓ Anti-static.



Weight	Gross weight (38) : 1000 g / Net Weight (38) : 782 g	
Size	35 to 39	40 to 42
Packaging	5 pairs	10 pairs
Box shoes (mm)	306 x 192 x 114	
Cartons (mm)	590 x 210 x 320	590 x 410 x 320