



JALBOHORT SAS JMJ01

S3 SRC EN ISO 20345:2011 35 to 47

- Full grain leather
- **Dual density Softane™ sole**
- **Antistatic and non-magnetic**



- Low Derby type shoe, black colour.
- Water-repellentfull grain leather upper, pull-up finish, thickness 1,9/2,1 mm.
- Quarters lined in "3D" a knitted three-dimensional fabric combined with foam for protection and comfort, and an open honeycomb structure for ventilation around the foot.
- Vamp lining in non-woven fabric. Resists scuffing and acid perspiration.
- Tongue in full grain leather, 3D lined.
- Fastens with 4 pairs of non-metallic eyelets. Black laces: 90 cm.
- Ergonomic collar padded with compact flexible foam.
- Ergonomic shoe, with broad synthetic polymer toecap, for saving on weight (50% lighter than steel). Impact resistance to 200 Joules.
- New manufacturing process: inner sole and insert in FleXtane™ By Jallatte perforation resistant material, antistatic, 100% composite. Sewn directly onto the bootstrap and covering 100% of the foot for all-round protection.
- Removable inlay, covering the entire surface of the foot, antistatic, anatomical and with shock-absorbent heel. High ability to absorb and evaporate perspiration.
- Heel stiffener to reinforce the heel seat.

Sole in dual-material Softane™ fitted with progressive effect shock absorber protecting the back and joints from vibrations.

Slip resistance tests results

EN Standard: EN ISO 20345: 2011

Requirement SRC (SRA+SRB)

SRA Test ground : ceramic / lubricant : water and detergent

On flat **0,45** (>0,32) – On the heel **0,33** (>0,28)

SRB Test ground steel / lubricant : glycerine On flat 0,20 (>0,18) - On the heel: 0,14 (>0,13)

- Comfort layer, density = 0.45.
- Wear layer, density = 1.10.
- Heel shock absorber 25 Joules
- Very high level of resistance to oils and hydrocarbons.
- Abrasion resistance 70 mm3.

Weight	Gross weight (42): 1354 g / Net weight (42): 1138 g			
Size	35 to 39	40	41 to 45	46 to 47
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	306 x 192 x 114		340 x 210 x 133	
Cartons (mm)	590 x 210 x 320	590 x 410 x 320	685 x 440 x 359	685 x 225 x 359



