

JMO08 JALCENTER SAS

S1P SRC
EN ISO 20345:2011
35 to 47

- **Velvet leather upper**
- **J-MODE PU / TPU transparent Sole**
- **Safety toe cap and midsole no metallic**
- **Antistatic**



- ❖ Urban-style grey colour shoe.
- ❖ Velvet leather upper and Canvas insert with laser brand Jallatte.
- ❖ Breathable upper lining in 3D mesh, with honeycomb structure for improved all-round ventilation of the foot and fast-drying.
- ❖ Vamp lining in non-woven fabric, resists scuffing and acid perspiration.
- ❖ Padded tongue for good instep protection, combined with two side bellows to prevent any dirt from getting into the boots.
- ❖ Padded ergonomic collar in compact flexible foam, lined for extra comfort and better ankle and Achilles tendon protection.
- ❖ Lace up on six pairs of eyelets. Laces : 120 cm. Leather lace-loop keeps tongue in place as you walk.
- ❖ Initial hygiene layer **Polyjal** covering the whole surface of the foot, removable, antistatic, antibacterially treated, anatomical and with heel shock absorbers.
- ❖ Ergonomic shoe with **broad synthetic polymer toe cap**, for saving on weight (50% lighter than steel) and removal of perspiration from around the forefoot. Impact resistance to **200 Joules**.
- ❖ New manufacturing **process** : antiperforation inner sole and insert in **FleXtane™ By Jallatte** material, antistatic, **100% composite**. Sewn directly onto the bootstrap and covering **100% of the foot** for all-round protection.
- 100% composite** materials: lighter than steel, non-magnetic, non-conductive of heat or cold.
- ❖ Heel stiffener to reinforce the heel seat
- ❖ Bi-component **Softane/ TPU transparent** sole. The expanded molecular structure of the Softane comfort layer ensures lightweight, supple footwear for walking.

Slip resistance tests results

EN Standard : EN ISO 20345 : 2011

Requirement SRC (SRA+SRB)

SRA Test ground : ceramic / lubricant : water and detergent

On flat **0,40** (>0,32) – On the heel **0,31** (>0,28)

SRB Test ground steel/lubricant : glycerine

On flat **0,30** (>0,18) – On the heel : **0,20** (>0,13)

- Thermoplastic PU transparent formulation over staples improves grip and offers excellent resistance to abrasion and very good grip in oil, fuel and grease.
- Central groove to channel away liquids and optimize adherence.
- Very flat sole with a large contact area with the ground. Improved stability
- Young look and maximum working comfort.
- Heel shock absorption 26 Joules

Weight	Gross weight (42) : 1370 g / Net weight (42) : 1183 g			
Size	35 to 39	40	41 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	306 x 192 x 114		340 x 210 x 133	
Cartons (mm)	590 x 210 x 320	590 x 410 x 320	685 x 440 x 359	685 x 225 x 359

