

JNU22 JALSPIN SAS ESD

S1P SRC EN ISO 20345:2011 38 to 47

- Synthetic nubuck / Textil
- Semelle J-nude PU / TPU
- Safety toe cap and midsole no metallic
- Antistatic and dissipative



- Low safety shoe, urban sport type, protecting the electronic devices against electrostatic discharge phenomena. Electrostatic dissipative shoes ESD Environmental Class II tested according to EN 61340-4-3 and EN 61340-5-1.
- Synthetic nubuck, Inserts and collar in technical textiles. Color grey / black. Silkscreened Jallatte applies.Pu reinforcement to the front of the sole.
- Upper lined in breathable 3D mesh with honeycomb structure to improve the peripheral ventilation of the foot, dries out rapidly.
- Padded tongue for good instep protection, combined with two side bellows to prevent any dirt from getting into the boots.
- Padded ergonomic collar in compact flexible foam, lined for extra comfort and better ankle and Achilles tendon protection.
- Lace up on 1 pair of eyelets and 3 pairs of fabric loops. Lace-loop keeps tongue in place as you walk. Black laces: 100 cm.
- Memory footbed made from BASF Elastopan polyurethane and heat-sensitive memory foam cushions pressure points, improves weight distribution and absorbs vibrations in the heel area. Anatomically formed and perforated.
- This is a DGUV 112-191 certified model, with the option of swapping the hygienic insole provided for a SECOSOL® orthopaedic insole.
- Ergonomic shoe with broad synthetic polymer toe cap, for saving on weight (50% lighter than steel) and removal of perspiration from around the forefoot. Impact resistance to 200 Joules.
- New manufacturing process: antiperforation inner sole and insert in FleXtane™ ESD By Jallatte material, antistatic, 100% composite. Sewn directly onto the bootstrap and covering 100% of the foot for all-round protection.

100% composite materials: lighter than steel, non-magnetic, non-conductive of heat or cold.

- Heel stiffener to reinforce the heel seat. **Innovative suole all in flexibility**, bi-component **Softane/TPU ESD** for natural foot movement.

Slip resistance tests results EN Standard: EN ISO 20345: 2011

Requirement SRC (SRA+SRB)

SRA Test ground: ceramic / lubricant: water and detergent

On flat 0,43 (>0,32) - On the heel 0,33 (>0,28)

SRB Test ground steel/lubricant : glycerine On flat **0,22** (>0,18) – On the heel **0,21** (>0,13)

- ➤ Lightweight and durable TPU outsole.
- ➤ Confort suole very flexible.
- ➤ Independents treads for high stability in every positions.
- > Gridded outsole for natural foot movement.
- ➤ High slip resistance with the grooves in the front and the back of the sole.

Weight	Gross weight (42): 1323 g / Net weight (42): 1115 g			
Size	38 to 39	40	41 to 45	46 to 47
Packaging	5 pairs	10 pairs 5 pairs		5 pairs
Box shoes (mm)	306 x 192 x 114		340 x 210 x 133	
Cartons (mm)	590 x 210 x 320	590 x 410 x 320	685 x 440 x 359	685 x 225 x 359



