



- Urban sport-style safety shoe incorporating **MAXI-Soft Duo™** anti-fatigue technology designed for work stations that require standing for long periods (Upright or sustained activity).
- Safety shoe protecting the electronic devices against electrostatic discharge phenomena. Electrostatic dissipative shoes ESD Environmental Class II tested according to **EN 61340-4-3** and **EN 61340-5-1**.
- Suede leather and breathable textile upper. Fluorescent markings on the back of the heel. Black color.
- Lining of the quarters in **OVER DRY** technical textile, very resistant and highly breathable.
- Non-woven textile forefoot lining.
- Padded ergonomic collar in compact flexible foam, lined for extra comfort and better ankle and Achilles tendon protection.
- Lace up on 5 pairs of non metal. Black laces 120 cm more blue laces in the box.
- Padded tongue for good instep protection, combined with two side bellows to prevent any dirt from getting into the boots.
- Perforated insole for enhanced comfort : **MAXI-Soft Duo™** composed of a soft **BASF® Dynamic PU** midsole with heat sensitive memory foam and a maximum size **BASF® Elastopan** insert that improves weight distribution by reducing pressure points and absorbs and relieves body stress associated with a prolonged standing working position and when walking. Anatomical, breathable and fitted with the **Link ESD™** system, an innovative and seamless, multi-contact, static electricity dissipater. (Patent pending).
- **FLEX-SYSTEM®** Stab-resistant structural insole and liner antistatic and 100% composite in compliance with standard 12568:2010.
- **LIGHT-PLUS®** protective toecap in synthetic material offering protection from an impact of 200 J



- **BASF® PU/PU** sole with an urban sport design, linear profile and excellent slip resistance.
- Extremely light and flexible support base.
- Constant energy return over the entire surface.
- Reduced feeling of fatigue due to posture.
- Relief that facilitates the evacuation of fluids.

Slip resistance tests results

EN Standard : EN ISO 20345 : 2011

Requirement SRC (SRA+SRB)

SRA Test ground : ceramic / lubricant : water and detergent
On flat **0,47** (>0,32)-On the heel **0,34** (>0,28)

SRB Test ground steel / lubricant : glycerine
On flat **0,33** (>0,18)-On the heel **0,21** (>0,13)

Weight	Gross Weight (42) : 1340 g / Net Weight (42) : 1134 g			
Size	35 to 39	40 to 41	42 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Box (mm)	306 x 192 x 114		340 x 210 x 133	
Dimensions (mm)	585 x 199 x 315	585 x 395 x 315	680 x 425 x 350	680 x 215 x 350