

## JYJY224 JALFARO SAS

S3 CI SRC  
EN ISO 20345:2011  
38 to 47

Spécial  
**BTP**



\* Brevet International Déposé

- Water-repellent full-grain leather
- **SINERGY** sole and insert **TPU Infinergy® de BASF**
- Aluminium toe cap / Antiperforation rustproof steel
- Antistatic

- ❖ Boot style outdoor, **designed with anti-fatigue technology** and **adapted to the building sector**. Brown and black color.
- ❖ Water-repellent full-grain leather upper, pull-up finish, thickness 1,8 / 2,0 mm. Protective scuff cap reinforcement to vamp and heel for strength and long life in very demanding conditions: improved resistance to impacts, cuts and abrasion. Pu reinforcement to the front of the sole.
- ❖ Warm fur for isothermal protection.
- ❖ Boot with 2 leather side tabs for rapid pull-on.
- ❖ Flat binding at top of quarters.
- ❖ **Memory** footbed made from **BASF Elastopan polyurethane** and heat-sensitive memory foam cushions pressure points, improves weight distribution and absorbs vibrations in the heel area. Anatomically formed and perforated.
- ❖ Heel stiffener to reinforce the heel seat.
- ❖ PREM-Alu tip in aluminium resisting an impact of an energy of 200 joules.
- ❖ **Stainless rustproof steel midsole**.
- ❖ **Innovative Synergy BTP** sole in bi-ingredient PU / and BASF Infinergy® E-TPU (Expanded Thermoplastic PolyUrethane) insert, with a remarkable capacity to reproduce more than 70% of the energy accumulated while (Bounce test **DIN 53512**).

### Slip resistance tests results

EN Standard : EN ISO 20345 : 2011

**Requirement SRC (SRA+SRB)**

**SRA** Test ground : ceramic / lubricant : water and detergent  
On flat **0,73** (>0,32) – On the heel **0,70** (>0,28)

**SRB** Test ground steel / lubricant : glycerine  
On flat **0,30** (>0,18) – On the heel: **0,28** (>0,13)

➤ Polyurethane outer sole with special crampons for outdoor jobs.

➤ **E-TPU** insert at low density of 0,25.

- High resistance to abrasion and stretching.
- Good chemical resistance.
- Long-term durability in a wide temperature range.
- **Dynamic performance in 3 phases: Shock Absorption - Accumulation of energy - Dynamic Return.**

Made with Infinergy® – the E-TPU from

**BASF**  
We create chemistry

Weight	Gross weight (42) : 1848 g / Net weight (42) : 1540 g
Size	38 to 47
Packaging	5 pairs
Box shoes (mm)	337 x 328 x 135
Cartons (mm)	625 x 425 x 345



 **Jallatte**®  
www.jallatte.com