



EU-TYPE EXAMINATION CERTIFICATE



The following model of Personal Protective Equipment has been subjected to an EU-type examination in accordance with the module B of the PPE regulation (2016/425) and has been shown to satisfy to essential health and safety requirements.

Certificate N° 0075/006/161/04/23/0582 EXT 01/04/23

Issued by CTC, Notified Body N°0075, to the following model of personal protective equipment :

Manufacturer : JALLATTE SAS
5, rue du Fort – Pierre JALLATTE 30170 SAINT HIPPOLYTE DU FORT
France

Description

PPE Type : *a safety footwear*
Product reference : JALMONT BETON EVOL SAS
Article code : 00J0254
Construction and material of outsole : INJECTED / POLYURETHANE

Pictures :



www.jallatte.com

JALMONT BETON EVOL SAS 00J0254

02/2023
00J0254

EN ISO 20345 : 2022

S3 FO SR

Made in Tunisia
JALLATTE SAS
5 Rue du Fort – Pierre Jallatte
30170 St Hippolyte du Fort
France

EPI II

Reference standard : EN ISO 20345:2022

Classification : I **Category : S3 FO SR**

Size range : 36-48

Toecap nature : Metallic **Insert nature : Metallic**

At the date of certificate the product is in compliance with Annex XVII of REACH regulation (n° 1907/2006 and revisions)

Full description of the PPE, reference rules verified in the context of the EU-type examination and information given on the product are detailed in the manufacturer's technical file index 01 dated from APRIL 2023 and the user instructions index Rev 05 - 02/2023.

NOTA : Any modification to new items of the personal protective equipment object of this EU type approval certificate or any modification of the information contained in the manufacturer technical file which served for the deliverance of the EU type approval certificate (change of address, change of company status) should be brought to the attention of the notified body in accordance with Annex V §7.2 of Regulation 2016/425. Any marking on the PPE which is not concerned by the Regulation (UE) 2016/425, is not covered by this certificate.

Issued in Lyon by

Séverine AUBERT

CE Expert Team Coordinator



Date of first issue : 25 July 2023

End of validity date : 25 July 2028



In application of the Regulation 2016/425 of the European parliament and the Council of 9th March 2016 related to Personal Protective Equipment and repealing the Directive 89/686/EEC.



Accreditation n° 5-0594
Scope available on:
www.cofrac.fr

www.ctcgroupe.com

cemarking@ctcgroupe.com

CTC - 4, rue Hermann Frenkel - 69367 Lyon cedex 07 - France
Tél. : +33 (0)4 72 76 10 10 - Fax : +33 (0)4 72 76 10 00 - ctclyon@ctcgroupe.com

Comité Professionnel de Développement Économique (CPDE) Cuir Chaussure Maroquinerie Ganterie
Loi 78-654 du 22.06.1978 - Siret 77564972600160 - Code NAF 9412Z - TVA FR 88775649726

JALLATTE SAS

MANUFACTURER'S TECHNICAL FILE

Reference of the product: JALMONT BETON EVOL SAS

Article code: 00J0254

Technical file index: 01

Last update: APRIL 2023

IDENTIFICATION

Reference of the product:	JALMONT BETON EVOL SAS
Article Code:	00J0254
This article is a major variant of the model:	00J0255 JALMONT EVOL SAS
Technical file index :	01
Last update :	APRIL 2023

Manufacturer

JALLATTE SAS

5, rue du Fort – Pierre JALLATTE 30170 SAINT HIPPOLYTE DU FORT

France

Tel : 33 (0)4.66.80.63.00

Tel : 33 (0)4.66.80.63.03

Factories

MARTEK SARL

ROUTE DE TUNIS - ZONE INDUSTRIELLE / 7050 MENZEL BOURGUIBA

Tunisie

Tel : 00 216 72 11 37 00

JALLATTE SAS

5, rue du Fort – Pierre JALLATTE 30170 SAINT HIPPOLYTE DU FORT

France

Tel : 33 (0)4.66.80.63.00

Fax : 33 (0)4.66.80.63.03

FOOTWEAR DESCRIPTION

Footwear description

The classification of this footwear is I : Footwear made from leather and other materials, excluding all-rubber or all-polymeric footwear.

The design of this footwear is B : ankle boot.

Visual description

General view :



Outsole view :



Reference of the mould : PF

Range of sizes

36-48

Construction and material of outsole

INJECTED / POLYURETHANE

Field of use

BTP / Maçonnerie

Risk assessment (Essential Health and Safety Requirement. Annex II - PPE Regulation)

		Applicable	Covered by	
§1	Requirements defined in the Annex II §1 are applicable to all PPE	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Standard
			<input checked="" type="checkbox"/>	Instruction for use
			<input checked="" type="checkbox"/>	Marking
§1.4	Manufacturer's instructions and information is available	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Standard
			<input checked="" type="checkbox"/>	Instruction for use
			<input type="checkbox"/>	Marking
§2.2	PPE is designed and manufactured in a way that perspiration resulting from use is minimised. Otherwise it must be equipped with means of absorbing perspiration.	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Standard
			<input checked="" type="checkbox"/>	Instruction for use
			<input type="checkbox"/>	Marking
§2.4	If it is known that the design performance of new PPE may be significantly affected by ageing, the month and year of manufacture and/or, if possible, the month and year of obsolescence must be indelibly and unambiguously marked on each item of PPE placed on the market and on its packaging.	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Standard
			<input checked="" type="checkbox"/>	Instruction for use
			<input checked="" type="checkbox"/>	Marking
§2.6	PPE is intended for use in potentially explosive atmospheres	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Standard
			<input checked="" type="checkbox"/>	Instruction for use
			<input checked="" type="checkbox"/>	Marking
§2.9	PPE incorporating components which can be adjusted or removed by the user	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Standard
			<input checked="" type="checkbox"/>	Instruction for use
			<input type="checkbox"/>	Marking
§2.12	PPE bearing one or more identification markings or indicators directly or indirectly relating to health and safety	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Standard
			<input checked="" type="checkbox"/>	Instruction for use
			<input checked="" type="checkbox"/>	Marking
§2.14	Multi-risk PPE	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Standard
			<input checked="" type="checkbox"/>	Instruction for use
			<input checked="" type="checkbox"/>	Marking
§3.1.1	The PPE is intended to protect against impact caused by falling or ejected objects and collisions of parts of the body with an obstacle	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Standard
			<input checked="" type="checkbox"/>	Instruction for use
			<input type="checkbox"/>	Marking
§3.1.2.1	The PPE is intended to protect against falls due to slipping	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Standard
			<input checked="" type="checkbox"/>	Instruction for use
			<input checked="" type="checkbox"/>	Marking
§3.2	The PPE is intended to protect against static compression of a part of the body	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Standard
			<input type="checkbox"/>	Instruction for use
			<input type="checkbox"/>	Marking
§3.3	The PPE is intended to protect against mechanical injuries	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Standard
			<input checked="" type="checkbox"/>	Instruction for use
			<input checked="" type="checkbox"/>	Marking

FOOTWEAR CONSTITUTION

	Reference	Material	Color
UPPER	PL00184	CROUPON VELOURS BETON RENARD S2 20/22 (vache) Cuir velours épaisseur 2.0/2.2	Marron
	SI00627	ANTIABRASION MICRO.LARICI COL. CUIR 2.0 S3 Toile 225 gr/mq. Composition 64% polyuréthane 36% poliamide	Marron
	AT00920	Passe-lacets DIN 01547 (fer)	Gris
COLLAR	SI00025 = SI00002	SYNTHETIQUE SPICE MARRONE Synthétique épaisseur 0.70/0.75 comp. CO 45	Marron
TONGUE	SI00025 = SI00002	SYNTHETIQUE SPICE MARRONE Synthétique épaisseur 0.70/0.75 comp. CO 45	Marron
VAMP LINING	SI00284	SUPERFASER MILLE GRIS doublure 260/gr 100% PES grammage 3gr/dmq	Gris
QUARTER LINING	SI00465	SURF BEIGE COL.413 doublure maille 3 D 260/gr 100% PES grammage 3gr/dmq	Beige
INSOLE	SP00012	1ère de montage ANTIST.2,2 MM JALLATTE antiperforation tissu aramide épaisseur 2.2 fournisseur DELTA BBD	Beige
INSOCK	TL00080	C/S.09983 AIR NERO ANT+TRANSF.JALL 1ère de propreté polyuréthane 100% expansé densité 0,40	Nero
OUTSOLE	CH 00116 / CH 00117	PU / PU	marron / beige
TOE CAP	PU00017	EMBOUT ACIER MOD 704 PERFORE	Gris
INSERT	LA00004	Semelle acier 160 INOX EPOXY ANTIST. antiperforation métallique	Gris

PROTECTION SCOPE

Basic requirements

This product has been designed to be a safety footwear.

The applicable basic requirements are detailed in the following standard(s):

- EN ISO 20345:2022 Safety footwear

This product is a category II PPE.

At the date of the certificate, the product is in compliance with Annex XVII of the European REACH regulation (n° 1907/2006 and revisions)

Additional requirements

The claimed additional requirements are :

- Closed seat region
- Cleated outsole
- Perforation resistance (metallic insert type P)
- Antistatic footwear
- Energy absorption of seat region
- Slip resistance (ceramic tile with glycerine)
- Upper : Water penetration and absorption of upper material
- Outsole : Fuel oil resistance

MARKING - PACKAGING

Information marked on the footwear

- * Logo of the Manufacturer
- * Logo **CE**
- * Manufacturer's name or commercial brand
- * Manufacturer's postal address
- * Manufacturer's type designation
- * Size
- * At least year and month of footwear manufacture
- * The number and year of the applicable specific standard(s)
- * The appropriate codes of marking according to the applicable requirements and additional protection and performance claimed

Marking example

CE
Jallatte®
www.jallatte.com
JALMONT BETON EVOL SAS 00J0254

02/2023
00J0254

EN ISO 20345 : 2022
S3 FO SR

Made in Tunisia
JALLATTE SAS
5 Rue du Fort – Pierre Jallatte
30170 St Hippolyte du Fort
France

EPI II



The location of the marking is : Etiquette piquée à l'intérieur de la chaussure + semelle
Method of marking on the footwear: Etiquette CE tissu piquée sur la doublure

Packaging

1 paire dans une boîte chaussure

References of test reports performed in order to verify the compliance with the requirements of the technical rules:

Laboratory	Reference	Laboratory	Reference
CIMAC	2017/1557-5-RP-2/4	CTC	L220405886_2
CIMAC	2017/1821-1-RP-2/4	CTC	L220610315_1
CIMAC	2018-0046-1-RP-2/3/4	CTC	L220916790_1
CIMAC	2021/1409-4-RP-1	CTC	L220917412_1
CTC	L211019729_1	CTC	L221020023_1
CTC	L211019734_1	CTC	L230202498_1
CTC	L211019739_1	RICOTEST	4053614.01
CTC	L220203149_1		

MEANS OF CONTROL

Essais en internes mensuels : Résistance électrique (méthode interne)- Perforation -Absorption d'énergie du talon, choc (EN ISO 20344: 2021).

Essais journaliers sur semelle : décollement bi-couche , abrasion, déchirement pantalon, flexion, dureté et densité (EN ISO 20344: 2021)

PPE subject to ageing :

The design performance of this product can be affected by ageing. The peremption period is estimated at Durée maximum de 7 ans conseillée dans notice CE when stored in appropriate conditions (humidity, temperature, clean , ventilated, light). Before use, the footwear shall be visually controlled, in case of deterioration the footwear must be scrapped (abrasion, cut, tear...).

Declaration of conformity :

The EU declaration of conformity can be accessed on the website: www.jallatte.com