



# EU-TYPE EXAMINATION CERTIFICATE



The following model of Personal Protective Equipment has been subjected to an EU-type examination in accordance with the module B of the PPE regulation (2016/425) and has been shown to satisfy to essential health and safety requirements.

**Certificate N° 0075/006/161/04/22/0686 EXT 01/05/22**

Issued by CTC, Notified Body N°0075, to the following model of personal protective equipment :

**Manufacturer :** JALLATTE SAS  
5, rue du Fort – Pierre JALLATTE 30170 SAINT HIPPOLYTE DU FORT  
France

### Description

**PPE Type :** *an occupational and personnel grounding, ESD control - footwear*

**Product reference :** JALNIGEL ESD

**Article code :** JOJO212

**Construction and material of outsole :** Polyuréthane - insert TPU

**Pictures :**



www.jallatte.com  
JALNIGEL ESD JOJO212

04/2021  
JOJO212

EN ISO 20347 : 2012

02 FO SRC

EN 61340-5-1 : 2016

Made in Tunisia  
JALLATTE SAS  
5 Rue du Fort – Pierre Jallatte  
30170 St Hippolyte du Fort  
France

EPI II



**Reference standard :** EN ISO 20347 : 2012 and EN 61340-5-1:2016

**Classification :** I **Category :** 02 FO SRC

**Size range :** 35 - 48 **Slip resistance :** SRC

**Toecap nature :** N/A **Insert nature :** N/A

**At the date of certificate the product is in compliance with Annex XVII of REACh regulation (n° 1907/2006 and revisions)**

Full description of the PPE, reference rules verified in the context of the EU-type examination and information given on the product are detailed in the manufacturer's technical file index 01 dated from AUGUST 2022 and the Instruction for Use index REV. 04 - 11/2021.

NOTA : Any modification to new items of the personal protective equipment object of this EU type approval certificate or any modification of the information contained in the manufacturer technical file which served for the deliverance of the EU type approval certificate (change of address, change of company status) should be brought to the attention of the notified body in accordance with Annex V §7.2 of Regulation 2016/425. Any marking on the PPE which is not concerned by the Regulation (UE) 2016/425, is not covered by this certificate.

**Issued in Lyon by**

**Date of first issue :** 18 August 2022

Didier GUISSADO

**End of validity date :** 18 August 2027

Certification and Quality Manager



In application of the Regulation 2016/425 of the European parliament and the Council of 9th March 2016 related to Personal Protective Equipment and repealing the Directive 89/686/EEC.



Accreditation n° 5-0594  
Scope available on:  
www.cofrac.fr

[www.ctcgroupe.com](http://www.ctcgroupe.com)

[cemarking@ctcgroupe.com](mailto:cemarking@ctcgroupe.com)

CTC - 4, rue Hermann Frenkel - 69367 Lyon cedex 07 - France  
Tél. : +33 (0)4 72 76 10 10 - Fax : +33 (0)4 72 76 10 00 - [ctclyon@ctcgroupe.com](mailto:ctclyon@ctcgroupe.com)

Comité Professionnel de Développement Économique (CPDE) Cuir Chaussure Maroquinerie Ganterie  
Loi 78-654 du 22.06.1978 - Siret 77564972600160 - Code NAF 9412Z - TVA FR 88775649726

**JALLATTE SAS**

# **MANUFACTURER'S TECHNICAL FILE**

**Reference of the product :** JALNIGEL ESD

**Article code :** JOJO212

**Technical file index :** 01

**Last update :** AUGUST, 2022

# IDENTIFICATION

Reference of the product: JALNIGEL ESD  
Article Code : JOJO212  
Major variant of model: JOJO205 JALSALT ESD  
Technical file index : 01  
Last update : AUGUST, 2022

## Manufacturer :

JALLATTE SAS

5, rue du Fort – Pierre JALLATTE 30170 SAINT HIPPOLYTE DU FORT

France

tel : 33 (0)4.66.80.63.00

fax : 33 (0)4.66.80.63.03

## Factory :

MARTEK SARL

ROUTE DE TUNIS - ZONE INDUSTRIELLE / 7050 MENZEL BOURGUIBA

Tunisie

Tel : 00 216 72 11 37 00

JALLATTE SAS

5, rue du Fort – Pierre JALLATTE 30170 SAINT HIPPOLYTE DU FORT

France

Tel : 33 (0)4.66.80.63.00

Fax : 33 (0)4.66.80.63.03

# FOOTWEAR DESCRIPTION

## Footwear description:

The classification of this footwear is: I : Footwear made from leather and other materials, excluding all-rubber or all-polymeric footwear  
The design of this footwear is: B : ankle boot

## Visual description:

General view :



Outsole view :



Reference of the mould : LJ ENERGY

## Range of sizes :

35 - 48

## Construction and material of outsole :

Polyuréthane - insert TPU

## Field of use

Métiers de bouche / Hygiène - Santé / Hotellerie - Restauration

Risk assessment (Essential Health and Safety Requirement. Annex II - PPE Regulation)				
		Applicable	Covered by	
§1	Requirements defined in the Annex II §1 are applicable to all PPE	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Standard
			<input checked="" type="checkbox"/>	Instruction for use
			<input checked="" type="checkbox"/>	Marking
§1.4	Manufacturer's instructions and information is available	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Standard
			<input checked="" type="checkbox"/>	Instruction for use
			<input type="checkbox"/>	Marking
§2.2	PPE is designed and manufactured in a way that perspiration resulting from use is minimised. Otherwise it must be equipped with means of absorbing perspiration.	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Standard
			<input checked="" type="checkbox"/>	Instruction for use
			<input type="checkbox"/>	Marking
§2.4	If it is known that the design performance of new PPE may be significantly affected by ageing, the month and year of manufacture and/or, if possible, the month and year of obsolescence must be indelibly and unambiguously marked on each item of PPE placed on the market and on its packaging.	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Standard
			<input checked="" type="checkbox"/>	Instruction for use
			<input checked="" type="checkbox"/>	Marking
§2.6	PPE is intended for use in potentially explosive atmospheres	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Standard
			<input checked="" type="checkbox"/>	Instruction for use
			<input checked="" type="checkbox"/>	Marking
§2.9	PPE incorporating components which can be adjusted or removed by the user	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Standard
			<input checked="" type="checkbox"/>	Instruction for use
			<input type="checkbox"/>	Marking
§2.12	PPE bearing one or more identification markings or indicators directly or indirectly relating to health and safety	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Standard
			<input checked="" type="checkbox"/>	Instruction for use
			<input checked="" type="checkbox"/>	Marking
§3.1.2.1	The PPE is intended to protect against falls due to slipping	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Standard
			<input checked="" type="checkbox"/>	Instruction for use
			<input checked="" type="checkbox"/>	Marking
§3.3	The PPE is intended to protect against mechanical injuries	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Standard
			<input checked="" type="checkbox"/>	Instruction for use
			<input checked="" type="checkbox"/>	Marking

# FOOTWEAR CONSTITUTION

	Ref	Material	Color
UPPER	SI 00678 = SI00701	PUTEK PLUS NERO FF WR FELTRO 350 putspider vesoft 350 wrgore 48%PA 47% PU 5% PL CMS:147 gr:1235/1354	Noir
	SI 00544	ANTIABRASION MICRO.LARICI NERO 2.0MM S3 Tela 225 gr/mq. Comp. PE 2/30 Kg MA 5gr/	Noir
COLLAR	SI 00544	ANTIABRASION MICRO.LARICI NERO 2.0MM S3 Tela 225 gr/mq. Comp. PE 2/30 Kg MA 5gr/	Noir
	SI 00330	ALBANY NERO ACC FELTRO 300 HYDRO Tela 225 gr/mq. Comp. PE 2/30 Kg MA 5gr/	Noir
TONGUE	SI 00002	SINTETICO SPICE NERO sintetico spessore 0.70/0.75 comp. CO 45% PU 55%	Noir
	SI 00544	ANTIABRASION MICRO.LARICI NERO 2.0MM S3 Tela 225 gr/mq. Comp. PE 2/30 Kg MA 5gr/	Noir
	SI 00330	ALBANY NERO ACC FELTRO 300 HYDRO Tela 225 gr/mq. Comp. PE 2/30 Kg MA 5gr/	Noir
VAMP LINING	SI 00743	SURF GRIGIO ACC TELA NERA fodera a tunnel d'aria 260/gr 100% PES 22gage massa areica 2,5gr/dmq	Gris
QUARTER LINING	SI 00568	ROMA gris 31 ACC ROV.+MTP4,5+ MGL noir MTP 80% + 20% MGL in PE épaisseur 0,5	Gris
	SI 00466	SURF NERO fodera a tunnel d'aria 260/gr 100% PES massa areica 3gr/dmq (tongue lining)	Noir
INSOCK	TL 00169 = TL 00170	C/SOTTOPIEDE SOFT GEL NERO fusbett poliuretano 100% espanso densità 0,40	Noir / Jaune
OUTSOLE	CH 00116 / CH 00117	PU / PU	Noir / Gris
	IN 00021 = IN 00009	INSERTO SUOLA INFINERGY BIANCO E-TPU Expanded thermoplastic polyuréthane densité 0,25	Blanc
INSOLE	SP00033	SOTTOPIEDE CONDUTTIVO 3,5mm ANTHRACITE sottopiede conduttivo polipropilene spessore 3,5 850gr/mq FORNITORE DELTA BBD	Gris
DECORATIVE ELEMENTS	AT 01413	TALLONETTA TPU JALLATTE SUPPORT N/G	Noir / Gris
	SV 00055	SERIGRAFIA JE ARGENTO/GRIGIO AT01434	Argent / Gris
	AT 00297	BORDINO N2267/12 COL. NERO	Noir

# PROTECTION SCOPE

## Basic requirements :

This product has been designed to be an occupational and personnel grounding, ESD control - footwear.

The technical rules are :

European Standard EN ISO 20344 : 2011 Personal protective equipment - test methods for footwear

European Standard EN ISO 20347 : 2012 : Personal protective equipment - Occupational footwear

EN 61340-5-1:2016

It is a category II product

Requirement of the standard EN ISO 20347 : 2012 concerning the value of the coefficient of friction of ceramic tiles floor with detergent solution and steel floor with glycerol (SRC)

Requirement of the paragraph 5.8.1. Design of the standard EN ISO 20347 : 2012 concerning cleated outsole.

At the date of certificate, the product is in compliance with Annex XVII of European REACH regulation (n° 1907/2006 and revisions)


## Additional requirements :

The additional requirements are :

- Closed seat region
- Antistatic footwear
- Energy absorption of seat region
- Upper : Water penetration and water absorption

# MARKING - PACKAGING

## Information printed on the footwear :

- \* Logo of the Manufacturer
- \* Logo 
- \* Manufacturer's type designation
- \* Postal address of manufacturer
- \* Footwear's reference JALNIGEL ESD
- \* Article code JOJO212
- \* Size
- \* Year of manufacture and at least quarter
- \* The number and year of the Standard used
- \* The symbol(s) of the additional requirements

## Marking example :



The location of marking is : Etiquette piquée à l'intérieur de la chaussure

## Method of marking on the footwear :

Etiquette CE tissu piquée sur la doublure

## Packaging :

1 paire dans une boîte chaussure

## References of test reports performed in order to verify the compliance with the requirements of the technical rules :

Laboratory	Reference	Laboratory	Reference
CIMAC	2018/0046-1-RP-2	CTC	L210713482_1
CIMAC	2018/1150-1-RP-2	CTC	L210713478_2
CIMAC	2017/1557-5-RP-2	CTC	L220201996_1
CTC	L210201913_2	CIMAC	2021/0646-13-RP-1
CIMAC	2021/1390-3-RP-1	CTC	L210814749_1
CTC	L210713488_2	CTC	L210713483_1
CIMAC	2017/1382-2-RP-2	CIMAC	2020/3109-13-RP-1
CTC	L210201930_1	CTC	L211120383_1
CIMAC	2020/2010-6-RP-1	CTC	L220508224_1
		CTC	L220814671_1



# MEANS OF CONTROL

Essais en internes mensuels : Résistance électrique ( méthode interne )- Perforation -Absorption d'énergie du talon, choc (EN ISO 20344: 2011).

Essais journaliers sur semelle : décollement bi-couche , abrasion, déchirement pantalon, flexion, dureté et densité (EN ISO 20344: 2011)

## **PPE subject to ageing :**

Peremption period : Durée maximum de 7 ans conseillée dans notice CE when stored in appropriate conditions (humidity, temperature, clean , ventilated, light). Before use, the footwear shall be visually controlled, in case of deterioration the footwear must be scrapped (abrasion, cut, tear, ...).

## **Declaration of conformity :**

Available on : [www.jallatte.com](http://www.jallatte.com)