

- Safety boot. Specifically designed for foundry work.
- Black leather upper.
- Lined with 3D.LINING<sup>®</sup>, a three-ply fabric for better extraction of moisture, very breathable and fast-drying.
- Vamp lining in non-woven fabric. Resists abrasion and acid perspiration.
- Collar lined and padded with flexible foam for better ankle protection.
- Front of foot protected by leather bellows covered with a spark arrester flap.
- Stitching strengthened with rivets.
- Adjustable closure system with Velcro straps.
- Soft footbed made of BASF Dynamic polyurethane with heat sensitive memory foam and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical, breathable and fitted.
- > LIGHT-PLUS<sup>®</sup> protective toecap in synthetic material offering protection from an impact of 200 J.
- Stab-resistant steel liner.
- Antisatic shoe.

Slip resistance tests results
EN Standard : EN ISO 20345 : 2011
Requirement SRC (SRA+SRB)
SRA Test ground : ceramic / lubricant : water
and detergent
On flat <b>0,40</b> (>0,32) – On the heel <b>0,31</b> (>0,28)
SRB Test ground steel / lubricant : glycerine On flat 0,29 (>0,18) – On the heel: 0,21 (>0,13)

**KOMPACT VIBRAM**<sup>®</sup> sole, designed and tested by Vibram<sup>®</sup>, made in high performance rubber compound to obtain a superb adherence and grip, the optimal durability and an avant-garde design.

Designed to face rough terrains, harsh environments, often in difficult weather conditions, this sole offers the best grip and reliability even on most demanding surfaces. Contact heat-resistance up to 300° C.

Weight	Gross weight (4	Gross weight (42): g / Net weight (42): g			
Size	35 to 39	40 to 41	42 to 45	46 to 48	
Packaging	5 pairs	10 pairs		5 pairs	
Box shoes (mm)	340 x 210 x 133		340 x 245 x 133		
Cartons (mm)	685 x 225 x 359	685 x 440 x 359	685 x 505 x 359	685 x 255 x 359	

