



ARCO ESD
54619

S1 SRC
EN ISO 20345:2011
35 to 47
Low shoe
Suede leather upper



SMART

- Ⓜ Low safety shoe, tennis type, protecting the electronic devices against electrostatic discharge phenomena. Electrostatic dissipative shoes **ESD Environmental Class II tested according to EN 61340-4-3 and EN 61340-5-1.** PU toe protection in front. Blue colour
- Ⓜ Suede leather upper Thickness 1,9 / 2,1. Perforated quarters for better foot ventilation.
- Ⓜ **3D.LINING**® in three-ply material for improved evacuation of moisture to the exterior, high breathability and fast-drying.
- Ⓜ Vamp lining in non-woven fabric. Resists abrasion and acid perspiration.
- Ⓜ Padded collar. Provides comfort to the ankle-bones and protects the Achilles tendon.
- Ⓜ Lace up on four pairs of lace stays. Laces grey 100 cm.
- Ⓜ Padded tongue to provide better protection to the instep, combined with two side gussets to prevent grit from entering the shoe.
- Ⓜ Complete **VENTO-PLUS**® ESD anatomical and antistatic inlay, with honeycomb structure for improved air circulation.
- Ⓜ **LIGHT-PLUS**® protective toe cap in synthetic material offering protection from an impact of 200 J.

Sole in PU dual density :

- Resists oils and hydrocarbons .
- Self-cleaning sole and deep multi-directional treads.
- Absorption of heel impact > 20 joules
- Wrap-around profile for better stability when walking

Slip resistance tests results	
EN Standard : EN ISO 20345 : 2011	
Requirement SRC (SRA+SRB)	
SRA Test ground : ceramic / lubricant : water and detergent	
On flat	0,42 (>0,32) – On the heel 0,30 (>0,28)
SRB Test ground steel / lubricant : glycerine	
On flat	0,27 (>0,18) – On the heel: 0,20 (>0,13)

Weight	Gross weight (42) : 1222 g / Net weight (42) : 1014 g			
Size	35 to 39	40 to 42	43 to 45	46 to 47
Packaging	5 pairs	10 pairs		5 pairs
Dimensions	585 x 199 x 315	585 x 395 x 315	680 x 425 x 350	680 x 215 x 350
Dimensions boites (mm)	306 x 192 x 114		340 x 210 x 133	