



MIRUS
007AX67

S3 SRC
EN ISO 20345:2011
38 to 47

High shoe
Trekking



- ⊗ High trekking safety shoe, black colour. PU toe protection in front and anti-abrasion leather for strength and long life.
- ⊗ Upper in finest-quality water-resistant leather, 1.9/2.1 mm. Grainy finish.
- ⊗ **3D.LINING®** in three-ply material for improved evacuation of moisture to the exterior, high breathability and fast-drying.
- ⊗ Vamp lining in non-woven fabric. Resists abrasion and acid perspiration.
- ⊗ Padded collar. Provides comfort to the ankle-bones and protects the Achilles tendon.
- ⊗ Fastened by lacing through four pairs of lace-stays and two pairs of metallic hooks. Laces 130 cm 36 to 41 and 150 cm 42 to 47.
- ⊗ Padded tongue to provide better protection to the instep, combined with two side gussets to prevent grit from entering the shoe.
- ⊗ **Soft** footbed made of **BASF Dynamic polyurethane** with heat sensitive memory foam and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical and breathable.
- ⊗ Stab-proof non-metallic **FLEX-SYSTEM®** liner : total protection of the sole of the foot.
- ⊗ **LIGHT-PLUS®** protective toecap in synthetic material offering protection from an impact of 200 J.

Slip resistance tests results

EN Standard : EN ISO 20345 : 2011 Requirement SRC
(SRA+SRB)

SRA Test ground : ceramic / lubricant : water and detergent
On flat **0,49** (>0,32) – On the heel **0,35** (>0,28)

SRB Test ground steel / lubricant : glycerine
On flat **0,26** (>0,18) – On the heel: **0,18** (>0,13)

W-Tech Wrapping Technology sole in PU dual density :

- Resists oils and hydrocarbons .
- Slim, streamlined profile rising towards the toes.
- Absorption of heel impact > 20 joules
- Wrap-around profile for better stability when walking



Weight	Gross weight (42) : 1416 g / Net weight (42) : 1198 g			
Size	35 to 39	40 to 41	42 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	340 x 210 x 133		340 x 245 x 133	
Cartons (mm)	685 x 225 x 359	685 x 440 x 359	685 x 505 x 359	685 x 255 x 359