

**MESH
7FR16**

**S1P SRC
EN ISO 20345:2011
35 to 47**

**Low shoe
Urban sport**



FREE

Fresh

3D Lining

**Light
PLUS**

**COMFORT
PLUS**

**FLEX SYSTEM
ZERO**

**metal
FREE**

- ⌚ Low urban sport safety shoe, grey colour. PU toe protection in front.
- ⌚ Suede leather upper Thickness 1,9 / 2,1. **Airnet®** textiles inserts for high breathability.
- ⌚ **3D.LINING®** in three-ply material for improved evacuation of moisture to the exterior, high breathability and fast-drying.
- ⌚ Vamp lining in non-woven fabric. Resists abrasion and acid perspiration.
- ⌚ Padded collar. Provides comfort to the ankle-bones and protects the Achilles tendon.
- ⌚ Fastened by lacing. Laces grey 100 cm.
- ⌚ Padded tongue in **Airnet®** to provide better protection to the instep, combined with two side gussets to prevent grit from entering the shoe.
- ⌚ Complete **COMFORT PLUS®** inlay, antistatic and anatomically shaped in flexible polyurethane covered in breathable, absorbent fabric.
- ⌚ Stab-proof non-metallic **FLEX-SYSTEM®** liner : total protection of the sole of the foot.
- ⌚ **LIGHT-PLUS®** protective toecap in synthetic material offering protection from an impact of 200 J.

Slip resistance tests results

EN Standard : EN ISO 20345 : 2011

Requirement SRC (SRA+SRB)

SRA Test ground : ceramic / lubricant : water and detergent

On flat **0,70** (>0,32) – On the heel **0,48** (>0,28)

SRB Test ground steel / lubricant : glycerine

On flat **0,23** (>0,18) – On the heel: **0,19** (>0,13)

Sole FREE in PU dual density :

- Resists oils and hydrocarbons .
- Innovative design, linear profile.
- Absorption of heel impact > 20 joules
- Wrap-around profile for better stability when walking



Weight	Gross Weight (42) : 1332 g / Net Weight (42) : 1124 g			
Size	35 to 39	40 to 41	42 to 45	46 to 47
Packaging	5 pairs	10 pairs		5 pairs
Box (mm)	306 x 192 x 114		340 x 210 x 133	
Dimensions (mm)	585 x 199 x 315	585 x 395 x 315	680 x 425 x 350	680 x 215 x 350