



**INOX L  
7SP06**

**S3 SRC  
EN ISO 20345:2011  
38 to 48**

**High shoe  
Water-repellent full-grain leather upper**

**SUPREME**



- Ⓜ High shoe, basket type, brown colour. PU toe protection in front.
- Ⓜ Water-repellent full-grain leather pull-up finish upper Thickness 1,9 / 2,1. Protective Stark scuff cap reinforcement to vamp for strength and long life in very demanding conditions: improved resistance to impacts, cuts and abrasion. Anti-abrasion PU scuff cap.
- Ⓜ **3D.LINING**® in three-ply material for improved evacuation of moisture to the exterior, high breathability and fast-drying.
- Ⓜ Vamp lining in non-woven fabric. Resists abrasion and acid perspiration.
- Ⓜ Padded collar. Provides comfort to the ankle-bones and protects the Achilles tendon.
- Ⓜ Lace up on five pairs of lace stays. Laces 120 cm.
- Ⓜ Padded tongue to provide better protection to the instep, combined with two side gussets to prevent grit from entering the shoe.
- Ⓜ Complete **COMFORT PLUS**® inlay, antistatic and anatomically shaped in flexible polyurethane covered in breathable, absorbent fabric.
- Ⓜ Stainless rustproof steel midsole.
- Ⓜ **LIGHT-PLUS**® protective toecap in synthetic material offering protection from an impact of 200 J.

Slip resistance tests results	
EN Standard : EN ISO 20345 : 2011	
Requirement <b>SRC</b> (SRA+SRB)	
<b>SRA</b> Test ground : ceramic / lubricant : water and detergent	
On flat <b>0,42</b> (>0,32) – On the heel <b>0,30</b> (>0,28)	
<b>SRB</b> Test ground steel / lubricant : glycerine	
On flat <b>0,27</b> (>0,18) – On the heel: <b>0,20</b> (>0,13)	

**Sole** in PU dual density :

- Resists oils and hydrocarbons .
- Self-cleaning sole and deep multi-directional treads.
- Absorption of heel impact > 20 joules
- Wrap-around profile for better stability when walking

Weight	Gross Weight (42) : 1588 g / Net Weight (42) : 1380 g			
Size	35 to 39	40 to 41	42 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Box (mm)	306 x 192 x 114		340 x 210 x 133	
Dimensions (mm)	585 x 199 x 315	585 x 395 x 315	680 x 425 x 350	680 x 215 x 350