



FORERUNNER 7TR02

S3 CI HI HRO SRC
EN ISO 20345:2011

Sizes 38 to 47

Ranger boots
All terrain style



- ⊗ All-terrain style ranger boots
- ⊗ Full-grain leather upper. Thickness 1.9/2.1 mm
- ⊗ **3D.LINING®**, a lining made of a material with three layers, with a network of micro-channels which envelop the feet and ensure breathability and moisture can pass through to the outside and **THINSULATE®** cold insulating and anti-cold fabric for a perfect thermic microclimate in every weather condition.
- ⊗ Padded collar in compact flexible foam for extra comfort and better ankle and Achilles tendon protection. **CONFORTPLUS®** footbed, full piece, antistatic, anatomic, in soft polyurethane covered with a special fibre with EVA reticular structure. The holes in the front area guarantee a perfect foot venting and the heel area combined with **IN-GEL SYSTEM®** helps preventing shocks to the spinal columns.
- ⊗ **FLEX-SYSTEM® Zéro** perforation resistant midsole in composite material with special ceramics. Non-magnetic, non-thermal, flexible and light weight, it protects 100 % of the foot surface.
- ⊗ **LIGHT-PLUS®** toe-cap, 200 Joule protection in composite material, light weight, non-magnetic, anti-corrosive and anti-allergic.

Slip resistance EN ISO 20345:2011
Qualité SRC (SRA+SRB)

SRA Test ground/Ceramic/lubricant
Water and detergent

On flat **0,40** (>0,32) - On the heel **0,31** (>0,28)

SRB Test ground : steel/lubricant
Glycerine

On flat **0,29** (>0,18) - On the heel **0,21** (>0,13)

KOMPAKT VIBRAM® sole, designed and tested by Vibram®, made in high performance rubber compound to obtain A superb adherence and grip, the optimal durability and an avant-garde design.

Designed to face rough terrains, harsh environments, often in difficult weather conditions, this sole offers the best grip and reliability even on most demanding surfaces. Contact heat-resistance up to 300° C.



Weight	Gross weight (42): 1858 g / Net weight (42): 1640 g							
Sizes	38 to 39	40	41	42	43	44	45	46 to 47
Packaging	5 pairs	10 pairs					5 pairs	
Dimensions	625X425X345		655X330X750				625X425X345	