



BRICK ESD
007TR15

S3 CI SRC
EN ISO 20345:2011
Sizes : 35 to 48



High shoe
Trekking



- Trekking type safety shoe. Double protective reinforcement, PU toe protection in front and anti-abrasion STARK® for strength and long life. Orange and brown colors.
- Electrostatic dissipative shoes ESD Environmental Class II tested according to EN 61340-4-3 and EN 61340-5-1 protecting the electronic devices against electrostatic discharge phenomena.
- Water-repellent full-grain leather upper, pull-up finish. **Excellent impermeability**, no water crossing after 7h test. Scuff-resistant protective **STARK®** reinforcement to vamp and heel.
- **3D.LINING®**, a lining made of a material with three layers, with a network of micro-channels which envelop the feet and ensure breathability and moisture can pass through to the outside and **THINSULATE®** cold insulating and anti-cold fabric for a perfect thermic microclimate in every weather condition.
- Padded collar lined for better protection of the ankles and Achilles tendon.
- Lace-up fastening system with 6 perforations. Laces 150 cm.
- Padded and lined tongue for instep protection with two side bellows to keep out dust and dirt.
- **Soft** footbed made of **BASF® Dynamic** polyurethane with heat sensitive memory foam and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical, breathable and fitted with the **Link ESD™** system, an innovative multi-contact static electricity dissipater (Patent pending).
- **FLEX-SYSTEM® Zéro** perforation resistant midsole in composite material with special ceramics. Non-magnetic, non-thermal, flexible and light weight, it protects 100 % of the foot surface.
- **LIGHT-PLUS®** toe-cap, 200 Joules protection in composite material, light weight, non-magnetic, anti-corrosive and anti-allergic.

Slip resistance tests results	
EN Standard : EN ISO 20345 : 2011 Requirement	
SRC (SRA+SRB)	
SRA Test ground/Ceramic/lubricant	
Water and detergent	
On flat 0,44 (>0,32) - On the heel 0,29 (>0,28)	
SRB Test ground : steel/lubricant	
Glycerine	
On flat 0,34 (>0,18) - On the heel 0,24 (>0,13)	

- Dual density **Softane™ PU** sole, **robust and versatile**, with progressive shock absorber and anti-twist heel reinforcement integrated.
- Comfort layer, density 0.45 / Outsole density = 1.10.
- High abrasion resistance .
- Highly resistant to oils and hydrocarbons.
- Heel shock absorbtion > 20 Joules.
- Rugged sole pattern with self-cleaning treads, depth 6,5 mm.
- Very flat sole with a large contact area with the ground. Improved stability.



Weight	Gross weight (42) : 1540 g / Net weight (42) : 1334 g			
Size	35 to 39	40 to 41	42 to 45	46 to 48
Packaging	5 pairs		10 pairs	5 pairs
Box shoes (mm)	340 x 210 x 133		340 x 245 x 133	
Cartons (mm)	680 x 215 x 350	680 x 425 x 350	685 x 500 x 350	685 x 250 x 350