



S3S CI LG FO SR
EN ISO 20345:2022
38 to 47

Half boot
Trekking



- Safety half boot. Double protective reinforcement, PU toe protection in front and anti-abrasion **STARK®** for strength and long life. Black and brown colors.
- Safety shoe protecting the electronic devices against electrostatic discharge phenomena. Electrostatic dissipative shoes **ESD** Environmental Class II tested according to **EN 61340-4-3/4-5/5-1**.
- Water-repellent full-grain leather upper, pull-up finish. **Excellent waterproof leather, no water crossing after 7h test**. Very good breathability (sweating well above the normative requirements).
- Flat binding at top of quarters.
- 2 leather side tabs for rapid pull-on.
- **3D.LINING®** Liner made of 3-layer material for better moisture transport to the outside, high breathability and quick drying.
- **Soft** footbed made of **BASF® Dynamic** polyurethane with heat sensitive memory foam and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical, breathable and fitted with the **Link ESD™** system, static electricity dissipater.
- The **FLEX-SYSTEM® S-type** mounting insole by **Jallatte** is puncture-resistant to sharp objects up to 3mm in diameter (Small) in compliance with standard **22568-4:2021**, antistatic, **100% composite**, sewn directly onto the upper and **covers 100% of the foot** for all-round protection.
- **LIGHT-PLUS® B** safety tip made of synthetic material protecting against a shock of 200 J. Minimum height after test ≥ 4mm in relation to the Type A toe cap in accordance with Standard **22568-2:2019**.

Slip resistance tests results

EN Standard : EN ISO 20345:2022

SRA Test ground/Ceramic/lubricant
Water and detergent

On flat **0,36** (>0,32) - On the heel **0,42** (>0,28)

SRB Test ground : steel/lubricant
Glycerine

On flat **0,23** (>0,18) - On the heel **0,33** (>0,13)

- Dual density **PU** sole, **robust and versatile**, with progressive shock absorber and anti-twist heel reinforcement integrated.
- Comfort layer, density 0.45 / Outsole density = 1.10.
- High abrasion resistance .
- Highly resistant to oils and hydrocarbons.
- Heel shock absorption > 20 Joules.
- Rugged sole pattern with self-cleaning treads, depth 6,5 mm.
- Very flat sole with a large contact area with the ground. Improved stability.

Weight	Gross weight (42) : 1696 g / Net weight (42) : 1390 g		
Size	35 to 39	40 to 45	46 to 48
Packaging	5 pairs	10 pairs	5 pairs
Box (mm)	365 x 320 x 133		
Dimensions (mm)	690 x 330 x 384	690 x 330 x 754	690 x 330 x 384

