



S3 CI HI HRO SRC
EN ISO 20345:2011
Sizes 38 to 47

High shoes
All terrain style



- High safety shoe all-terrain style, black color.
- Full-grain leather upper. Thickness 1.9/2.1mm. PU reinforcement to the front of the sole.
- **3D.LINING®**, a lining made of a material with three layers, with a network of micro-channels which envelop the feet and ensure breathability and moisture can pass through to the outside and **THINSULATE®** cold insulating and anti-cold fabric for a perfect thermic microclimate in every weather condition.
- Padded collar in compact flexible foam for extra comfort and better ankle and Achilles tendon protection.
- Padded and lined leather tongue for instep protection with two side bellows to keep out dust and dirt.
- Fastened by five pairs of non metallics lace stays. Laces : 120 cm.
- **Soft** footbed made of **BASF Dynamic polyurethane** with heat sensitive memory foam and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical, breathable and fitted.
- **FLEX-SYSTEM® Zéro** perforation resistant midsole in composite material with special ceramics. Non-magnetic, non-thermal, flexible and light weight, it protects 100 % of the foot surface.
- **LIGHT-PLUS®** toe-cap, 200 Joules protection in composite material, light weight, non-magnetic, anti-corrosive and anti-allergic.

Slip resistance tests results

EN Standard : EN ISO 20345 : 2011

Requirement SRC (SRA+SRB)

SRA Test ground/Ceramic/lubricant
Water and detergent

On flat **0,40** (>0,32) - On the heel **0,31** (>0,28)

SRB Test ground : steel/lubricant
Glycerine

On flat **0,29** (>0,18)- On the heel **0,21** (>0,13)

KOMPACT VIBRAM® sole, designed and tested by Vibram®, made in high performance rubber compound to obtain a superb adherence and grip, the optimal durability and an avant-garde design.

Designed to face rough terrains, harsh environments, often in difficult weather conditions, this sole offers the best grip and reliability even on most demanding surfaces.

Contact heat-resistance up to 300° C.



Weight	Gross weight (42) : 1550 g / Net weight (42) : 1380 g			
Size	38 to 39	40 to 41	42 to 45	46 to 47
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	340 x 210 x 133		340 x 245 x 133	
Cartons (mm)	685 x 225 x 359	685 x 440 x 359	685 x 505 x 359	685 x 255 x 359