



**MARSHALL
ABI01**

S1P SRC
EN ISO 20345:2011
38 to 47

**Sporty urban safety shoes
Antistatic**

24 BIT

OVERDRY

COMFORT^{PLUS}

ALULITE[®]

FLEX^{system}_{ZERO}

- ⦿ Beige and green sporty urban safety shoes .
- ⦿ Suede leather upper and AIR TEACH insert . Perforated quarters for better foot ventilation.
- ⦿ Upper lined in technical textiles OVER DRY, very resistant and high breathability.
- ⦿ Vamp lined in non-woven fabric.
- ⦿ Padded collar with compact flexible foam for extra comfort and better ankle and Achilles tendon protection..
- ⦿ Closure by laces. Laces : 120 cm.
- ⦿ Padded and lined textile tongue for instep protection with side bellows to keep out dust and dirt.
- ⦿ **CONFORTPLUS[®]** footbed single-block structure made of soft polyurethane with absorbent and breathable fabric textile, anatomical and antistatic.
- ⦿ This is a **DGUV 112-191** certified model, with the option of swapping the hygienic insole provided for a **SECOSOL[®]** orthopaedic insole.
- ⦿ **FLEX-SYSTEM[®]** Stab-resistant structural insole and liner antistatic and 100% composite in compliance with standard 12568:2010.
- ⦿ **ALU-LITE[®]** 200 J aluminium safety toe cap, anti corrosion and 50% lighter than steel material.



98GRIP

Slip resistance tests results

EN Standard : EN ISO 20345 : 2011

Requirement SRC (SRA+SRB)

SRA Test ground : ceramic / lubricant : water and detergent

On flat **0,98** (>0,32) – On the heel **0,74** (>0,28)

SRB Test ground steel / lubricant : glycerine

On flat **0,40** (>0,18) – On the heel: **0,35** (>0,13)

Dual density PU sole , outsole in PU transparent.

- ▶ Out-sole design featuring specific transversal grooves, high performance of slip resistance.
- ▶ Resistant to oils and hydrocarbons.
- ▶ Sporty profile and design.
- ▶ Heel shock absorbtion > 20 Joules.

Weight	Gross Weight (42) : 1282 g / Net Weight (42) : 1074 g		
Size	38 to 39	40 to 41	42 to 45
Packaging	5 pairs	10 pairs	5 pairs
Box (mm)	306 x 192 x 114		
Dimensions (mm)	585 x 199 x 315	585 x 395 x 315	680 x 425 x 350
			680 x 215 x 350