

24 BIT



CALVIN ESD s
00ABI06

S3S FO SR
EN ISO 20345:2022
35 to 48

Black sporty urban safety shoes
Antistatic



- Low safety shoe, urban sport type, protecting the electronic devices against electrostatic discharge phenomena. **Electrostatic dissipative shoes ESD Environmental Class II** tested according to EN 61340-4-3 and EN 61340-5-1.
- Water-repellent full-grain leather upper, pull-up finish.
- Upper lined in technical textiles OVER DRY, very resistant and high breathability.
- Vamp lined in non-woven fabric.
- Padded collar with compact flexible foam for extra comfort and better ankle and Achilles tendon protection..
- Fluorescent markings for increased visibility when doing night work.
- Closure by laces. Laces : 120 cm.
- Bellows tongue for superior waterproofing. Padded tongue to protect the top of the foot.
- **Soft** footbed made of **BASF Dynamic polyurethane** with heat sensitive memory foam and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical and breathable.
- This is a **DGUV 112-191** certified model, with the option of swapping the hygienic insole provided for a **SECOSOL®** orthopaedic insole.
- The **FLEX-SYSTEM® S-type** mounting insole by Jallatte is puncture-resistant to sharp objects up to 3mm in diameter (Small) in compliance with standard **22568-4:2021**, antistatic, 100% composite, sewn directly onto the upper and covers 100% of the foot for all-round protection.
- **ALU-LITE® type B 200 J** aluminium safety toe cap, anti corrosion and 50% lighter than steel material.

98GRIP



Dual density PU sole , outsole in PU transparent.

- ▶ Out-sole design featuring specific transversal grooves, high performance of slip resistance.
- ▶ Resistant to oils and hydrocarbons.
- ▶ Sporty profile and design.
- ▶ Heel shock absorbtion > 20 Joules.

Slip resistance tests results EN Standard ISO 20345:2022

Test ground : Ceramic / NaLS (Sodium lauryl sulfate)

A- Heel to the front **0,48** (≥ 0,31)

B- Front to back **0,44** (≥ 0,36)

Additional requirement SR : Ceramic /Glycerin

C - Heel to the front **0,34** (≥ 0,19)

D- Front to back **0,24** (≥ 0,22)

Weight	Gross Weight (42) : 1294 g / Net Weight (42) : 1086 g			
Size	35 to 39	40 to 41	42 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Box (mm)	335 x 210 x 130		335 x 245 x 130	
Dimensions (mm)	680 x 234 x 356	685 x 440 x 356	680 x 514 x 356	685 x 256 x 356