



**SNOOP
ABI07**

**S1P SRC
EN ISO 20345:2011
35 to 48**

**Blue sporty urban safety shoes
Antistatic**

24 BIT

OVERDRY

**COMFORT
PLUS**

ALU-LITE

**FLEXsystem
ZERO**

- Ⓞ Blue sporty urban safety shoes .
- Ⓞ Suede leather upper with technical textiles inserts .
- Ⓞ Upper lined in technical textiles **OVER DRY**, very resistant and high breathability.
- Ⓞ Vamp lined in non-woven fabric.
- Ⓞ Padded collar with compact flexible foam for extra comfort and better ankle and Achilles tendon protection..
- Ⓞ Fluorescent markings for increased visibility when doing night work.
- Ⓞ Closure by laces. Laces : 120 cm.
- Ⓞ Bellows tongue for superior waterproofing. Padded tongue to protect the top of the foot.
- Ⓞ **CONFORTPLUS**® footbed single-block structure made of soft polyurethane with absorbent and breathable fabric textile, anatomical and antistatic.
- Ⓞ This is a **DGUV 112-191** certified model, with the option of swapping the hygienic insole provided for a **SECOSOL**® orthopaedic insole.
- Ⓞ **FLEX-SYSTEM**® Stab-resistant structural insole and liner antistatic and 100% composite in compliance with standard 12568:2010.
- Ⓞ **ALU-LITE**® 200 J aluminium safety toe cap, anti corrosion and 50% lighter than steel material.



Dual density PU sole , outsole in PU transparent.

- ▶ Out-sole design featuring specific transversal grooves, high performance of slip resistance.
- ▶ Resistant to oils and hydrocarbons.
- ▶ Sporty profile and design.
- ▶ Heel shock absorbtion > 20 Joules.

Slip resistance tests results

EN Standard : EN ISO 20345 : 2011

Requirement SRC (SRA+SRB)

SRA Test ground : ceramic / lubricant : water and detergent

On flat **0,98** (>0,32) – On the heel **0,74** (>0,28)

SRB Test ground steel / lubricant : glycerine

On flat **0,40** (>0,18) – On the heel: **0,35** (>0,13)

Poids	Brut (42) : 1264 g / Net (42) : 1056 g			
Pointure	35 au 39	40 au 42	43 au 45	46 au 48
Conditionnement	5 paires	10 paires		5 paires
Dimensions cartons (mm)	585 x 199 x 315	585 x 395 x 315	680 x 425 x 350	680 x 215 x 350
Dimensions boites (mm)	306 x 192 x 114		340 x 210 x 133	