



**WAYNE
ABI16**

**S3 SRC
EN ISO 20345:2011
35 to 47**

**Low shoe urban sport style
Antistatic**

24 BIT

OVERDRY

**COMFORT
PLUS**

**ALU
LITE**

**FLEX
system
ZERO**

- Ⓢ Low safety shoe, urban sport style.
- Ⓢ Water resistant microfiber. White color.
- Ⓢ Upper lined in technical textiles OVER DRY, very resistant and high breathability.
- Ⓢ Vamp lined in non-woven textile.
- Ⓢ Padded collar with compact flexible foam for extra comfort ankle and Achilles tendon .
- Ⓢ Closure by laces. Laces 120 cm.
- Ⓢ Padded bellows tongue provides total waterproofness and protection for the top of the foot.
- Ⓢ **COMFORTPLUS**® footbed single-block structure made of soft polyurethane with absorbent and breathable fabric textile, anatomical and antistatic.
- Ⓢ This is a **DGUV 112-191** certified model, with the option of swapping the hygienic insole provided for a **SECOSOL**® orthopaedic insole.
- Ⓢ Stab-proof non-metallic **FLEX-SYSTEM**® zéro liner : total protection of the sole of the foot, in compliance with **standard 12568:2010**.
- Ⓢ **ALU-LITE**® protective toe cap in aluminum offering protection from an impact of 200 J.



Dual density PU sole , outsole in PU transparent.

- ▶ Out-sole design featuring specific transversal grooves, high performance of slip resistance.
- ▶ Resistant to oils and hydrocarbons.
- ▶ Sporty profile and design.
- ▶ Heel shock absorption > 20 Joules.

Slip resistance tests results

EN Standard : EN ISO 20345 : 2011

Requirement SRC (SRA+SRB)

SRA Test ground : ceramic / lubricant : water and detergent

On flat **0,98** (>0,32) – On the heel **0,74** (>0,28)

SRB Test ground steel / lubricant : glycerine

On flat **0,40** (>0,18) – On the heel: **0,35** (>0,13)

Weight	Gross Weight (42) : 1324 g / Net Weight (42) : 1166 g			
Size	35 to 39	40 to 41	42 to 45	46 to 47
Packaging	5 pairs		10 pairs	
Box (mm)	306 x 192 x 114		340 x 210 x 133	
Dimensions (mm)	585 x 199 x 315	585 x 395 x 315	680 x 425 x 350	680 x 215 x 350