


**DIDDY
ABI17**
**S3 SRC
EN ISO 20345:2011
38 to 47**
**Low shoe urban sport style
Antistatic**
24 BIT
OVERDRY
COMFORT^{PLUS}
ALULITE[®]
FLEX^{system}_{ZERO}

- ⦿ Low shoe, urban sport style.
- ⦿ Water resistant leather, pull-up finish and inserts in water-repellent technical textiles . Brown color.
- ⦿ Upper lined in technical textiles OVER DRY, very resistant and high breathability.
- ⦿ Vamp lined in non-woven textile.
- ⦿ Padded collar with compact flexible foam for extra comfort ankle and Achilles tendon .
- ⦿ Closure by laces. Laces 120 cm.
- ⦿ Padded bellows tongue provides total waterproofness and protection for the top of the foot.
- ⦿ **CONFORTPLUS[®]** footbed single-block structure made of soft polyurethane with absorbent and breathable fabric textile, anatomical and antistatic.
- ⦿ This is a **DGUV 112-191** certified model, with the option of swapping the hygienic insole provided for a **SECOSOL[®]** orthopaedic insole.
- ⦿ Stab-proof non-metallic **FLEX-SYSTEM[®] zéro** liner : total protection of the sole of the foot, in compliance with **standard 12568:2010**.
- ⦿ **ALU-LITE[®]** protective toe cap in aluminum offering protection from an impact of 200 J.


Dual density PU sole, outsole in PU transparent.

- ▶ Out-sole design featuring specific transversal grooves, high performance of slip resistance.
- ▶ Resistant to oils and hydrocarbons.
- ▶ Sporty profile and design.
- ▶ Heel shock absorbtion > 20 Joules.

98GRIP
Slip resistance tests results

 EN Standard : EN ISO 20345 : 2011
Requirement SRC (SRA+SRB)
SRA Test ground : ceramic / lubricant : water and detergent

 On flat **0,98** (>0,32) – On the heel **0,74** (>0,28)

SRB Test ground steel / lubricant : glycerine
 On flat **0,40** (>0,18) – On the heel: **0,35** (>0,13)

Weight	Gross Weight (42) : 1294 g / Net Weight (42) : 1086 g		
Size	35 to 39	40 to 41	42 to 45
Packaging	5 pairs	10 pairs	5 pairs
Box (mm)	306 x 192 x 114		340 x 210 x 133
Dimensions (mm)	585 x 199 x 315	585 x 395 x 315	680 x 425 x 350
			680 x 215 x 350