



**MASE  
ABI18**

**S1P SRC  
EN ISO 20345:2011  
38 to 47**

**Black sporty urban safety shoes  
Antistatic**

**24 BIT**

**DURABREATH**

**OVERDRY**

**COMFORT PLUS**

**ALULITE**

**FLEXsystem ZERO**

- ⊗ Black sporty urban safety shoes .
- ⊗ Suede leather upper with technical textiles inserts in **DURABREATH** .
- ⊗ Upper lined in technical textiles **OVER DRY**, very resistant and high breathability.
- ⊗ Vamp lined in non-woven fabric.
- ⊗ Padded collar with compact flexible foam for extra comfort and better ankle and Achilles tendon protection..
- ⊗ Fluorescent markings for increased visibility when doing night work.
- ⊗ Closure by laces. Laces : 120 cm.
- ⊗ Bellows tongue for superior waterproofing. Padded tongue to protect the top of the foot.
- ⊗ **CONFORTPLUS**® footbed single-block structure made of soft polyurethane with absorbent and breathable fabric textile, anatomical and antistatic.
- ⊗ This is a **DGUV 112-191** certified model, with the option of swapping the hygienic insole provided for a **SECOSOL**® orthopaedic insole.
- ⊗ **FLEX-SYSTEM**® Stab-resistant structural insole and liner antistatic and 100% composite in compliance with standard 12568:2010.
- ⊗ **ALU-LITE**® 200 J aluminium safety toe cap, anti corrosion and 50% lighter than steel material.



**Dual density PU sole** , outsole in PU transparent.

- ▶ Out-sole design featuring specific transversal grooves, high performance of slip resistance.
- ▶ Resistant to oils and hydrocarbons.
- ▶ Sporty profile and design.
- ▶ Heel shock absorbtion > 20 Joules.

**Slip resistance tests results**

EN Standard : EN ISO 20345 : 2011

**Requirement SRC (SRA+SRB)**

**SRA** Test ground : ceramic / lubricant : water and detergent

On flat **0,98** (>0,32) – On the heel **0,74** (>0,28)

**SRB** Test ground steel / lubricant : glycerine

On flat **0,40** (>0,18) – On the heel: **0,35** (>0,13)

Weight	Gross Weight (42) : 1254 g / Net Weight (42) : 1046 g			
Size	38 to 39	40 to 41	42 to 45	46 to 47
Packaging	5 pairs	10 pairs		5 pairs
Box (mm)	306 x 192 x 114		340 x 210 x 133	
Dimensions (mm)	585 x 199 x 315	585 x 395 x 315	680 x 425 x 350	680 x 215 x 350