

DYNAMIC



MANTIS
00DYC18

S1P SRC
EN ISO 20345:2011
36 to 48

Low shoe
Suede leather



- ❖ Blue safety shoe. PU toe protection in front.
- ❖ Suede leather upper, textile inserts. Perforated quarters and top of upper for better foot ventilation.
- ❖ **3D.LINING®** in three-ply material for improved evacuation of moisture to the exterior, high breathability and fast-drying.
- ❖ Vamp lining in non-woven fabric. Resists abrasion and acid perspiration.
- ❖ Padded collar. Provides comfort to the ankle-bones and protects the Achilles tendon.
- ❖ Lace up on four pairs of metallic eyelets . Laces 100 cm.
- ❖ Padded tongue to provide better protection to the instep, combined with two side gussets to prevent grit from entering the shoe.
- ❖ Complete **VENTO-PLUS®** anatomical and antistatic inlay, with honeycomb structure for improved air circulation.
- ❖ Stab-proof non-metallic **FLEX-SYSTEM® zéro** liner : total protection of the sole of the foot.
- ❖ **Patented 200 Joules safety toe cap.**

Slip resistance tests results

EN Standard : EN ISO 20345 : 2011

Requirement SRC (SRA+SRB)

SRA Test ground : ceramic / lubricant : water and detergent

On flat **0,40** (>0,32) – On the heel **0,36** (>0,28)

SRB Test ground steel / lubricant : glycerine

On flat **0,19** (>0,18) – On the heel: **0,14** (>0,13)

Sole in PU dual density :

- Resists oils and hydrocarbons .
- Self-cleaning sole and deep multi-directional treads.
- Absorption of heel impact > 20 joules
- Wrap-around profile for better stability when walking

Weight	Gross weight (42) : 1434 g /		Net weight (42) : 1226 g	
Size	36 to 39	40 to 41	42 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Dimensions (mm)	680 x 215 x 350	685 x 425 x 350	685 x 500 x 350	685 x 250 x 350
Dimensions box (mm)	340 x 210 x 133		340 x 245 x 133	

