

JALMARS SAS

00J0246

TRIFTANE

Tradition



S3 HRO SRC
EN ISO 20345:2011
36 to 47



- Full grain leather
- **Triftane™ Sole**
- **Toecap and antiperforation rustproof steel**
- **Antistatic**

- ❖ Black all purpose sporty ankle boots.
- ❖ Water-repellent full-grain leather upper. Thickness 1.9/2.1mm. Minimal stitching for increased watertightness and resistance to spilled and splashed liquids.
- ❖ Padded ergonomic collar in compact flexible foam, lined for extra comfort and better ankle and Achilles tendon protection.
- ❖ "3D" inner lining, combining foam for comfort and protection and an open structure (mesh panel) that improves air flow around the foot.
- ❖ Lace up on five pairs of stainless steel triangles with leather bellows tongue for superior waterproofing. Black / red laces :100 cm.
- ❖ Vamp lined in non-woven fabric. Resists scuffing and acid perspiration.
- ❖ Counter to maintain a snug-fitting heel.
- ❖ Initial hygiene layer covering the whole surface of the foot, removable, antistatic, antibacterially treated, anatomical and with heel shock absorbers. Capability of absorbing and removing high levels of perspiration.
- ❖ Stainless steel midsole.
- ❖ Patented 200 Joules safety toe cap with perforations, 9th width.
- ❖ **TRIFTANE™ sole technology** with a high adherence coefficient :
 The studs in the **TRIFTANE™** sole have sharp ridges to break the film of fluid that can form between the sole and the floor. Their shape and distribution ensure permanent contact with the floor.

Slip resistance tests results	
EN Standard : EN ISO 20345 : 2011	
Requirement SRC (SRA+SRB)	
SRA Test ground : ceramic / lubricant : water and detergent	
On flat 0,49 (>0,32) – On the heel 0,55 (>0,28)	
SRB Test ground steel / lubricant : glycerine	
On flat 0,19 (>0,18) – On the heel: 0,17 (>0,13)	

- **Abrasion resistance : 81mm³.**
- NBR shore hardness : 60
- The protective NBR grid ensures the solidity of the whole to extend its useful life.
- **Heel shock absorbtion 28 Joules**
- Hollow heel, the hollowed out centre area makes wearers feel lighter as they walk.
- Softane™ comfort layer, density 0.45
- **All purpose :**
 Resistant to oils and hydrocarbons, and acids and bases at low concentrations. Resistant to direct contact heat up to **300°C.**
 - Antistatic



www.jallatte.com

Weight	Gross weight(42): 1510 g / Net weight (42): 1240 g			
Size	36 to 39	40 to 42	43 to 45	46 to 47
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	342 x 213 x 114		350 x 245 x 133	
Cartons (mm)	590 x 220 x 348	590 x 437 x 348	685 x 500 x 355	685 x 250 x 358