



S3 HRO SRC
EN ISO 20345:2011
36 to 47



- **Full grain leather**
- **Triftane™ sole**
- **Toecap and antiperforation rustproof steel**
- **Antistatic**

- ❖ All purpose derby shoes. Black colour.
- ❖ Water-repellent full-grain leather upper. Thickness 1.9/2.1mm. Minimal stitching for increased watertightness and resistance to spilled and splashed liquids.
- ❖ Padded ergonomic collar in compact flexible foam, lined for extra comfort and better ankle and Achilles tendon protection.
- ❖ "3D" inner lining, combining foam for comfort and protection and an open structure (mesh panel) that improves air flow around the foot.
- ❖ Lace up on four pairs of eyelets over a leather tongue. Black / red laces :90 cm.
- ❖ Vamp lined in non-woven fabric. Resists scuffing and acid perspiration.
- ❖ Counter to maintain a snug-fitting heel.
- ❖ Initial hygiene layer covering the whole surface of the foot, removable, antistatic, antibacterially treated, anatomical and with heel shock absorbers. Capability of absorbing and removing high levels of perspiration.
- ❖ Stainless steel midsole
- ❖ Patented 200 Joule safety toecap with perforations, 9th width
- ❖ **TRIFTANE™ sole technology** with a high adherence coefficient :
- ❖ The studs in the **TRIFTANE™** sole have sharp ridges to break the film of fluid that can form between the sole and the floor. Their shape and distribution ensure permanent contact with the floor.

- **Abrasion resistance : 81mm3.**

- NBR shore hardness : 60

- The protective NBR grid ensures the solidity of the whole to extend its useful life.

- **Heel shock absorption 28 Joule**

- Hollow heel, the hollowed out centre area makes wearers feel lighter as they walk.

- Softane™ comfort layer, density 0.45

- All purpose :

Resistant to oils and hydrocarbons, and acids and bases at low concentrations. Resistant to direct contact heat up to **300°C.**

- Antistatic

Slip resistance tests results

EN Standard : EN ISO 20345 : 2011

Requirement SRC (SRA+SRB)

SRA Test ground : ceramic / lubricant : water and detergent

On flat **0,57** (>0,32) – On the heel **0,56** (>0,28)

SRB Test ground steel / lubricant : glycerine

On flat **0,26** (>0,18) – On the heel: **0,35** (>0,13)

Weight	Gross Weight (42): 1400 g / Net weight (42): 1130 g			
Size	36 to 39	40 to 42	43 to 45	46 to 47
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	342 x 213 x 114		350 x 245 x 133	
Cartons (mm)	590 x 220 x 348	590 x 437 x 348	685 x 500 x 355	685 x 250 x 358

