



S3 HI HRO SRC
EN ISO 20345:2011
38 to 47



SPÉCIFIQUE
ENROBÉS



- Full grain leather
- Triftane™ sole
- Toecap and antiperforation rustproof steel
- Antistatic

- ❖ Black and red safety boot specifically designed for working on hot surfaces.
- ❖ Full grain leather upper, thickness 1.9 / 2.1 mm. Minimal stitching for increased watertightness and resistance to splashed liquids and hydrocarbons.
- ❖ Fluorescent markings on the back of the heel for increased visibility when doing night work.
- ❖ Ergonomic padded collar with compact flexible foam for extra comfort and better ankle and Achilles tendon protection.
- ❖ Lace-up with 5 pairs of rustproof d-loops. Leather bellows for complete watertightness and to keep out liquids or particles. Red and grey reflective laces : 80 cm.
- ❖ Padded bellows tongue provides total waterproofness and protection for the top of the foot and keeps out fluids and particles.
- ❖ Vamp lined in non-woven textile resistant to abrasion and perspiration acids.
- ❖ Heel stiffener to reinforce the heel seat.
- ❖ **ISOLTANE™** anti-static lasting sole : A multi-layer insulating compound, made of:
 - a thermal screen of polyacrylonitrile non-woven fibres and viscose fibres
 - an insulating layer, composed of an aluminium heat dissipator, a non-woven cellulose material, latex foam and fleece
 Interior temperature rises **12,5°C** after 30 mins exposure on surface to 150°C. (Standard EN 344 requires an increase of < 22°C).
- ❖ Initial hygiene layer covering the whole surface of the foot, removable, antistatic, antibacterially treated, anatomical and with heel shock absorbers. Capability of absorbing and removing high levels of perspiration.
- ❖ Stainless steel midsole
- ❖ Patented 200 Joule safety toecap, 9th width
- ❖ **TRIFTANE™ VIBRAM** sole technology with a high adherence coefficient. Versatility of use. New formulation for increased durability.
 - Better mechanical resistance to abrasion, peeling and tearing.
 - NBR shore hardness : 60
 - Optimum grip level.
 - Hyperfunctional studs.
 - Heel shock absorbtion 28 Joules
 - Hollow heel, the hollowed out centre area makes wearers feel lighter as they walk.
 - Softane™ comfort layer, density 0.45
 - Resistant to oils and hydrocarbons, and acids and bases at low concentrations.
 - Resistant to direct contact heat up to 300°C.

Slip resistance tests results

EN Standard : EN ISO 20345 : 2022

Tiled floor / Water and detergent

From heel to toe **0,63** (>0,31)

From the forefoot to the back **0,58** (>0,36)

Tiled floor / Glycerine

From heel to toe **0,34** (>0,19)

From the forefoot to the back **0,27** (>0,22)

Weight	Gross Weight (42): 1510 g / Net weight (42): 1240 g			
Size	38 - 39	40 to 42	43 to 45	46 to 47
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	342 x 213 x 114		350 x 245 x 133	
Cartons (mm)	590 x 220 x 348	590 x 437 x 348	685 x 500 x 355	685 x 250 x 358

