

JALMONT BETON SAS J0253

S3 SRC
EN ISO 20345:2011
39 to 47

Softane™
Tradition



- **Full grain leather**
- **Dual-density Softane™ sole**

- ❖ Brown, heavy duty ankle boots.
- ❖ Water-repellent full grain leather upper stitched to the flesh side to resist laitance in cement and concrete. Thickness 2.2 mm.
- ❖ Padded collar, lined for better protection of the ankles and Achilles tendon, and greater walking comfort.
- ❖ Lace-up with 5 pairs of stainless triangles. Laces : 90 cm.
- ❖ Padded bellows tongue provides total waterproofness and protection for the top of the foot.
- ❖ Counter to maintain a snug-fitting heel.
- ❖ Vamp lined in non-woven fabric. Resists scuffing and acid perspiration.
- ❖ Inlay covering the entire surface of the foot, removable, antistatic, treated against bacteria, containing active carbon, anatomical and with heel cushioning. High capacity for absorbing and evaporating perspiration.
- ❖ Perforated steel toe-cap (patented) – 200 J.
- ❖ Puncture-resistant stainless steel midsole .
- ❖ Dual density **Softane™** sole with progressive shock absorber to protect back and joints from vibrations. Self cleaning sole pattern. Multi-directional treads. Rounded heel pressure zone for comfort and stability

Slip resistance tests results

EN Standard : EN ISO 20345 : 2011

Requirement SRC (SRA+SRB)

SRA Test ground : ceramic / lubricant : water and detergent

On flat **0,58** (>0,32) – On the heel **0,54** (>0,28)

SRB Test ground steel / lubricant : glycerine

On flat **0,37** (>0,18) – On the heel: **0,14** (>0,13)

- ✓ Wraps round the foot for increased stability when walking.
- ✓ Outsole density = 1.02 / Comfort layer density = 0.45
- ✓ Highly resistant to oils and hydrocarbons.
- ✓ Abrasion resistance : 80 mm³
- ✓ Heel shock absorption 29 Joules.

Weight	Gross weight (42): 1420 g / Net weight (42): 1250 g			
Size	39	40 to 42	43 to 45	46 to 47
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	342 x 213 x 114		350 x 245 x 133	
Cartons (mm)	590 x 220 x 348	590 x 437 x 348	685 x 500 x 355	685 x 250 x 358

