

S3 FO SR
EN ISO 20345:2022
36 to 48



- Full-grain leather
- Dual-density **Softane™ sole**
- Metal toe cap and puncture-resistant insert
- Antistatic



- ❖ High safety boot of the brodequin type, brown color. **Special construction.**
- ❖ Water-repellent full grain leather upper stitched to the flesh side to resist laitance in cement and concrete. Thickness : 2.2 mm. Abrasion-resistant heel.
- ❖ Padded collar, fully leather lined for better protection of the ankles and Achilles tendon, and greater walking comfort.
- ❖ Lace-up fastening with 5 pairs of rustproof triangles. Lace : 90 cm.
- ❖ Leather bellows for complete watertightness and to keep out liquids or particles.
- ❖ Upper lined in breathable **3D mesh** with honeycomb structure to improve the peripheral ventilation of the foot, dries out rapidly.
- ❖ Initial hygiene layer covering the whole surface of the foot, removable, antistatic, antibacterially treated, anatomical and with heel shock absorbers. Capability of absorbing and removing high levels of perspiration.
- ❖ **Stainless rustproof steel midsole.**
- ❖ **Perforated steel tip** (patented) – 9th width – Withstands an impact of 200 joules. Minimum height after test $\geq 4\text{mm}$ in relation to the Type A toe cap in accordance with **Standard 22568-1:2019.**
- ❖ **Heel stiffener to reinforce the heel seat.**
- ❖ Dual density **Softane™ sole** with progressive shock absorber to protect back and joints from vibrations.

Slip resistance tests results EN Standard ISO 20345:2022

Test ground : Ceramic / NaLS (Sodium lauryl sulfate)

A- Heel to the front **0,36** ($\geq 0,31$)

B- Front to back **0,65** ($\geq 0,36$)

Additional requirement SR : Ceramic /Glycerin

C - Heel to the front **0,23** ($\geq 0,19$)

D- Front to back **0,25** ($\geq 0,22$)

- ✓ **Density** : Tread layer = 1.02 / Comfort layer density = 0.45.
- ✓ Very good resistance to oils and hydrocarbons.
- ✓ Abrasion resistance : 80 mm³.
- ✓ Wraparound tread pattern for improved stability when walking.
- ✓ Self-cleaning tread pattern. Multi-directional lugs.
- ✓ Rounded heel at the point of contact for a smoother gait. Heel shock absorption : 29 joules.

Weight	Gross weight (42) : 1420 g / Net weight (42) : 1250 g			
Size	36 to 39	40	41 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	335 x 210 x 130		335 x 244 x 130	
Cartons (mm)	680 x 234 x 356	685 x 440 x 356	680 x 514 x 356	685 x 256 x 356