

**JALFRIGG**  
**00J0652**

**Softane**  
Avant-Garde



**S3S SC CI LG FO SR**  
**EN ISO 20345:2022**  
**35 to 48**



**0%**  
**METAL**

- Full grain **AP 23** leather
- **Softane™** dual-density sole
- Polymère toe cap type **B** and midsole no metallic
- Antistatic

- ❖ Fur-lined boots, natural colour, with 2 side pull straps for making them easier to pull on.
- ❖ Bootstrap in full grain leather **AP 23**, water and oil resistant : a Jallatte exclusive
  - ❖ **10 to 15% thicker** (2.4mm) than most leathers usually used in safety shoe manufacture.
  - ❖ **Upper resistance to water penetration:** to European standard level or more.
- ❖ Isothermic lining for better positive protection against the cold.
- ❖ Flat binding at top of quarters.
- ❖ The polyurethane toe cap, having been **SC**-rated, complies with EN ISO 20345:2021, which guarantees the footwear's sturdiness and longevity, as well as its increased resistance to impacts and scuffing.
- ❖ Two side tabs make them easy to pull on.
- ❖ **Soft** footbed made of **BASF Dynamic polyurethane** with heat sensitive memory foam and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical, breathable.
- ❖ Ergonomic shoe with broad toe-cap **SPRINGTANE type B** polymer tip for weight savings (50% lighter than steel). Resistant to a shock of 200 Joules. Minimum height after test  $\geq 4$ mm in relation to the Type A toe cap in accordance with Standard 22568-2 : 2021.
- ❖ **The FleXtane™ S-type** mounting insole by Jallatte is puncture-resistant to sharp objects up to **3mm** in diameter (Small) in compliance with standard 22568-4:2021, antistatic, 100% composite, sewn directly onto the upper and covers 100% of the foot for all-round protection.
- ❖ Heel stiffener to reinforce the heel seat.
- ❖ Dual-density **Softane™** sole with progressive heel shock absorber to protect back and joints from vibrations. Self cleaning sole pattern. Multi-directional treads. Rounded heel pressure zone for comfort and stability. Sole features with the **JAL'GRIP SYSTEM**, a LADDER GRIP double-release unhooking system as standard, is fully **LG**-rated in compliance with standard EN ISO 20345:2021, which enables ladder attachment and prevents the risk of falls from heights.

**Slip resistance tests results EN Standard ISO 20345:2022**

Test ground : Ceramic / NaLS (Sodium lauryl sulfate)  
A- Heel to the front **0,35** ( $\geq 0,31$ )  
B- Front to back **0,55** ( $\geq 0,36$ )

**Additional requirement SR** : Ceramic /Glycerin  
C - Heel to the front **0,22** ( $\geq 0,19$ )  
D- Front to back **0,26** ( $\geq 0,22$ )

- ❖ Density of comfort layer = 0.45 / Density of wearing layer = 1.10
- ❖ Heel shock absorption > 20 Joules
- ❖ Wrap-around profile for better stability when walking
- ❖ Highly resistant to oil and hydrocarbons
- ❖ Abrasion resistance 75 mm3
- ❖ Stainless steel midsole

Weight	Gross weight (42) : 1532 g / Net weight (42) : 1314 g	
Size	35 à 45	46 au 48
Packaging	5 pairs	
Box shoes (mm)	337 x 328 x 135	365 x 320 x 134
Cartons (mm)	625 x 425 x 343	690 x 330 x 383



**Jallatte®**

www.jallatte.com