

J-Smarter

JALPALME SAS JDR12

S3 SRC
EN ISO 20345:2011
38 to 47

- Full grain leather
- J-Smarter PU single-density sole



- ❖ Black safety shoe, derby type. Straight toe-cap.
- ❖ Classic and elegant design.
- ❖ Water-repellent full-grain leather upper, 1,5/ 1,7 mm thick.
- ❖ Leather lining quarter.
- ❖ Lined full grain leather tongue.
- ❖ Vamp lined in non-woven fabric. Resists scuffing and acid perspiration.
- ❖ Fastens with black laces : 75 cm.
- ❖ **J-confort**, anatomic footbed in soft micro-channelled material, lined with breathable and abrasion-resistant Vita- Plus fabric.. Antistatic.
- ❖ Heel stiffener to reinforce the heel seat.
- ❖ Stab-resistant **FleXtane™** insole and liner by Jallatte, antistatic, 100 % composite. Sewn directly onto the upper and covering 100 % of the foot for total protection.
- ❖ 200 Joules steel toe-cap

Slip resistance tests results

EN Standard : EN ISO 20345 : 2011

Requirement SRC (SRA+SRB)

SRA Test ground : ceramic / lubricant : water and detergent

On flat **0,34** (>0,32) – On the heel **0,29** (>0,28)

SRB Test ground steel / lubricant : glycerine

On flat **0,19** (>0,18) – On the heel: **0,15** (>0,13)

Single density polyuréthane sole :

- Highly resistant to oils and hydrocarbons
- The pattern design is purposed made to enhance comfort while waling and standing.
- Abrasion resistant.
- Heel-shock absorption > 20 Joules.



| | | | | |
|----------------|---|-----------------|-----------------|-----------------|
| Weight | Gross weight (42) : 1218 g / Net weight (42) : 1000 g | | | |
| Size | 38 to 39 | 40 | 41 to 45 | 46 to 47 |
| Packaging | 5 pairs | 10 pairs | | 5 pairs |
| Box shoes (mm) | 306 x 192 x 114 | | 340 x 210 x 133 | |
| Cartons (mm) | 590 x 210 x 320 | 590 x 410 x 320 | 685 x 440 x 359 | 685 x 225 x 359 |