

TRIFTANE™ Fighter

JALSABRE X2 JJ706

S3 CI HRO SRC
EN ISO 20345:2011
38 to 47



- Water-repellent full grain leather
- TRIFTANE™ Fighter sole

- ❖ Black urban sport boot.
- ❖ Water-repellent full grain leather upper, pull-up finish, 1,9 / 2,1 mm thick.
- ❖ Breathable upper lining in 3D mesh, with honeycomb structure for improved all-round ventilation of the foot and fast-drying.
- ❖ Padded ergonomic collar in compact flexible foam, lined for extra comfort and better ankle and Achilles tendon protection.
- ❖ Padded tongue for good instep protection, combined with two side bellows to prevent any dirt from getting into the boots.
- ❖ Lace up on six pairs of non-metallic eyelets. Laces : 150 cm.
- ❖ Heel stiffener to reinforce the heel seat.
- ❖ J-Multitech footbed : single-block structure made of soft polyurethane and designed to support the foot movement for maximum comfort and energy absorption, especially in the heel area. Perforated in the front part for improved ventilation.
- ❖ Xetane™ 200 Joule toe-cap, 100% composite fibre. Non-magnetic, lightweight.
- ❖ FleXtane™ By Jallatte anti-perforation inner sole and insert 100 % composite, yielding and flexible, non-detectable, non-magnetic and 70 % lighter than steel. Directly sewn to the bootstrap for 100% protection of the whole surface of the foot.
- ❖ 100% composite materials: lighter than steel, amagnetic, non-conductive of heat and cold.
- Triftane™ Fighter sole : innovative multifunctional outsole, made of 3 different parts, with a high slip resistant coefficient :

- The Oxytane comfort layer increases the softness, flexibility and the cushioning capacity thanks to its specific density and high concentration of closed cells which absorb heel shocks and vibrations.
- The NBR outsole (Nitrile Butadiene rubber) keeps from fatigue and improves adherence. The innovative position of the sole pattern follows the foot's natural motion for better grip on any surface, besides preventing dirt and liquid from lying under the soke.
- The NBR protective grid reinforces the entire structure and improves the shoe's durability, contact heat resistant to 300°C.

Slip resistance tests results

EN Standard : EN ISO 20345 : 2011

Requirement SRC (SRA+SRB)

SRA Test ground : ceramic / lubricant : water and detergent
On flat **0,50** (>0,32) – On the heel **0,48** (>0,28)

SRB Test ground steel / lubricant : glycerine
On flat **0,35** (>0,18) – On the heel: **0,25** (>0,13)



www.jallatte.com

| | | | | |
|----------------|--|-----------------|-----------------|-----------------|
| Weight | Gross weight (42): 1440 g / Net weight(42): 1222 g | | | |
| Size | 38 to 39 | 40 to 42 | 43 to 45 | 46 to 47 |
| Packaging | 5 pairs | 10 pairs | | 5 pairs |
| Box shoes (mm) | 342 x 213 x 114 | | 350 x 245 x 133 | |
| Cartons (mm) | 590 x 220 x 348 | 590 x 437 x 348 | 685 x 500 x 355 | 685 x 250 x 358 |