

JALIROK SAS JJE17

S3 CI AN HI HRO SRC
EN ISO 20345:2011
38 to 47

- **Water-repellent full-grain leather**
- **Sole Vibram® J-ESCAPE**
- **Polymère toe cap / Antiperforation rustproof steel**
- **Antistatic**



- ❖ High-laced boot style outdoor, **adapted to the building sector**. Brown and black color.
- ❖ Water-repellent full-grain leather upper, pull-up finish, thickness 1,8 / 2,0 mm. Protective scuff cap reinforcement to vamp and heel for strength and long life in very demanding conditions: improved resistance to impacts, cuts and abrasion. Pu reinforcement to the front of the sole.
- ❖ Ankle protector system on each side of the shoe. Inside result 5,9 kN, outside result 5,9 kN.
- ❖ Padded collar with compact flexible foam for extra comfort and better ankle and Achilles tendon protection.
- ❖ Fastened by 4 pairs of lace stays and 2 pairs of open hooks. Laces 130 cm.
- ❖ Padded, "3D" lined leather tongue to protect the top of the foot, with side bellows to keep out dust and dirt.
- ❖ Tabs at the back for easy pull-on.
- ❖ Upper lined in breathable 3D mesh with honeycomb structure to improve the peripheral ventilation of the foot, dries out rapidly.
- ❖ Vamp lined in non-woven fabric. Resists scuffing and acid perspiration.
- ❖ J-Multitech footbed : single-block structure made of soft polyurethane and designed to support the foot movement for maximum comfort and energy absorption, especially in the heel area. Perforated in the front part for improved ventilation and lined with an anti-abrasion fabric. Anatomically designed and anti-static.
- ❖ Heel stiffener to reinforce the heel seat.
- ❖ Ergonomic shoe, with broad synthetic polymer toe cap **SPRINGTANE** , for saving on weight (50% lighter than steel). Impact resistance to 200 Joules.
- ❖ **Stainless rustproof steel midsole.**
- ❖ **Sole J-ESCAPE™ VIBRAM CAPU** with **progressive effect shock-absorber** to protect the back and joints from vibrations . Pu reinforcement to the front of the sole.

Slip resistance tests results

EN Standard : EN ISO 20345 : 2011

Requirement SRC (SRA+SRB)

SRA Test ground : ceramic / lubricant : water and detergent

On flat **0,40** (>0,32) – On the heel **0,31** (>0,28)

SRB Test ground steel / lubricant : glycerine

On flat **0,29** (>0,18) – On the heel: **0,21** (>0,13)

- ◆ **Softane™** comfort layer
- ◆ Density = 0.45. Ensures comfortable walking for the wearer. Helps to absorb vibrations and provided heat insulation to the sole of the foot.
- ◆ Ground contact layer in **Néotril™** :
- ◆ Very highly resistant to oils, greases and conducted heat (300°C)
- ◆ Highly scuff- resistant.
- ◆ Sole very resistant to hydrocarbons.

Weight	Gross weight (42) : 1728 g / Net weight (42) : 1520 g			
Size	38 to 39	40	41 to 45	46 to 47
Packaging	5 pairs	10 pairs		5 pairs
Carton (mm)	340 x 210 x 133		340 x 245 x 133	
Box shoe (mm)	685 x 225 x 359	685 x 440 x 359	685 x 505 x 359	685 x 255 x 359

