

S3 CI HI HRO SRC
EN ISO 20345:2011
38 to 47



- **Water-repellent full-grain leather**
- **Sole Vibram® J-ESCAPE**
- **Polymère toe cap type B / Antiperforation rustproof steel**
- **Antistatic**

- ❖ Safety shoe, derby type style outdoor, **adapted to the building sector**. Brown and black color.
- ❖ Water-repellent full-grain leather upper, pull-up finish, thickness 1,8 / 2,0 mm. Protective scuff cap reinforcement to vamp and heel for strength and long life in very demanding conditions: improved resistance to impacts, cuts and abrasion. Pu reinforcement to the front of the sole.
- ❖ Padded collar with compact flexible foam for extra comfort and better ankle and Achilles tendon protection.
- ❖ Fastened by 4 pairs of lace stays. Laces 90 cm.
- ❖ Padded, "3D" lined leather tongue to protect the top of the foot, with side bellows to keep out dust and dirt.
- ❖ Upper lined in breathable **3D Surf** mesh with honeycomb structure to improve the peripheral ventilation of the foot, dries out rapidly.
- ❖ Vamp lined in non-woven fabric. Resists scuffing and acid perspiration.
- ❖ **Soft** footbed made of **BASF Dynamic polyurethane** with heat sensitive memory foam and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical, breathable and fitted
- ❖ Heel stiffener to reinforce the heel seat.
- ❖ Ergonomic shoe with **broad synthetic polymer toe cap type B**, for saving on weight (50% lighter than steel) Impact resistance to **200 Joules**. Minimum height after test $\geq 4\text{mm}$ in relation to the Type A toe cap in accordance with Standard 22568-2:2021.
- ❖ **Stainless rustproof steel midsole**.
- ❖ **Sole J-ESCAPE™ VIBRAM CA/PU** with **progressive effect shock-absorber** to protect the back and joints from vibrations . Pu reinforcement to the front of the sole.

Slip resistance tests results

EN Standard : EN ISO 20345 : 2011

Requirement SRC (SRA+SRB)

SRA Test ground : ceramic / lubricant : water and detergent

On flat **0,40** (>0,32) – On the heel **0,31** (>0,28)

SRB Test ground steel / lubricant : glycerine

On flat **0,29** (>0,18) – On the heel: **0,21** (>0,13)

- **Softane™** comfort layer
- Density = 0.45. Ensures comfortable walking for the wearer. Helps to absorb vibrations and provided heat insulation to the sole of the foot.
- Ground contact layer in **Néotril™** :
- Very highly resistant to oils, greases and conducted heat (300°C)
- Highly scuff- resistant.
- Sole very resistant to hydrocarbons.

Weight	Gross weight (42) : 1668 g / Net weight (42) : 1460 g			
Size	38 to 39	40	41 to 45	46 to 47
Packaging	5 pairs	10 pairs		5 pairs
Carton (mm)	306 x 192 x 114		340 x 210 x 133	
Box shoe (mm)	590 x 210 x 320	590 x 410 x 320	685 x 440 x 359	685 x 225 x 359

