

S3 CI HI HRO SRC
EN ISO 20345:2011
38 to 47



- **Water-repellent full-grain leather**
- **Sole Vibram® J-ESCAPE**
- **Polymère toe cap type B / Antiperforation rustproof steel**
- **Antistatic**

- ❖ Boot style outdoor **adapted to the building sector**. Brown and black color.
- ❖ Water-repellent full-grain leather upper, pull-up finish, thickness 1,8 / 2,0 mm. Protective scuff cap reinforcement to vamp and heel for strength and long life in very demanding conditions: improved resistance to impacts, cuts and abrasion. Pu reinforcement to the front of the sole.
- ❖ Warm fur for isothermal protection.
- ❖ Boot with 2 leather side tabs for rapid pull-on.
- ❖ Flat binding at top of quarters.
- ❖ **Soft** footbed made of **BASF Dynamic polyurethane** with heat sensitive memory foam and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical, breathable
- ❖ Ergonomic shoe with **broad synthetic polymer toe cap type B**, for saving on weight (50% lighter than steel) Impact resistance to **200 Joules**. Minimum height after test $\geq 4\text{mm}$ in relation to the Type A toe cap in accordance with Standard 22568-2:2021.
- ❖ Heel stiffener to reinforce the heel seat.
- ❖ **Stainless rustproof steel midsole**.
- ❖ **Sole J-ESCAPE™ VIBRAM CA/PU** with **progressive effect shock-absorber** to protect the back and joints from vibrations . Pu reinforcement to the front of the sole.

Slip resistance tests results

EN Standard : EN ISO 20345 : 2011
Requirement SRC (SRA+SRB)

SRA Test ground : ceramic / lubricant : water and detergent

On flat **0,40** (>0,32) – On the heel **0,31** (>0,28)

SRB Test ground steel / lubricant : glycerine

On flat **0,29** (>0,18) – On the heel: **0,21** (>0,13)

- **Softane™** comfort layer
- Density = 0.45. Ensures comfortable walking for the wearer. Helps to absorb vibrations and provided heat insulation to the sole of the foot.
- Ground contact layer in **Néotril™** :
- Very highly resistant to oils, greases and conducted heat (300°C)
- Highly scuff- resistant.
- Sole very resistant to hydrocarbons.

Weight	Gross weight (42) : 1903 g / Net weight (42) : 1606 g
Size	38 to 47
Packaging	5 pairs
Box shoes (mm)	337 x 328 x 135
Cartons (mm)	625 x 425 x 345

