

JALACER 00JJE23

J-ESCAPE

GORE-TEX®

S7S SC CI HI HRO LG FO SR
EN ISO 20345:2022
38 to 48



- leather upper pull-up finish
- **Vibram® J-ESCAPE** sole
- Antistatic
- **Type B polymer end cap and non-metallic puncture protection S**

- ❖ Full-grain water-repellent leather upper with pull-up finish, thickness 1.8/2.0 mm. **Excellent waterproof leather, no water crossing after 7h test.** Very good breathability (sweating well above the normative requirements). Abrasion-resistant leather toe cap and lower shaft.
- ❖ Brown, lace-up all terrain hiking boots with an original design, for unpredictable situations and frequent changes in weather. Height of the rod 190 mm. Color brown/ black.
- ❖ The polyurethane toe cap, having been **SC-rated**, complies with **EN ISO 20345:2021**, which guarantees the footwear's sturdiness and longevity, as well as its increased resistance to impacts and scuffing.
- ❖ Lining : **GORE-TEX®** Performance Comfort footwear membrane this protective membrane is waterproof but allows the foot to breathe. It acts as a windbreak, avoiding the feeling of cold when moisture is drawn out.
- ❖ Ergonomic padded collar with compact flexible foam for extra comfort and better ankle and Achilles tendon protection.
- ❖ Padded and lined leather tongue for instep protection with side bellows to keep out dust and dirt.
- ❖ Closure with lacing on 6 pairs of metal eyelets. 150 cm water-repellent black laces.
- ❖ **Soft** footbed made of **BASF® Dynamic** polyurethane with heat sensitive memory foam and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical and breathable.
- ❖ **Ergonomic** shoe with broad toe-cap **SPRINGTANE type B** polymer tip for weight savings (50% lighter than steel). Resistant to a shock of 200 Joules. Minimum height after test ≥ 4 mm in relation to the Type A toe cap in accordance with **Standard 22568-2:2019**.
- ❖ **The FlexTane™ S-type** mounting insole by **Jallatte** is puncture-resistant to sharp objects up to **3mm in diameter (Small)** in compliance with standard **22568-4:2021**, antistatic, **100% composite**, sewn directly onto the upper and **covers 100% of the foot** for all-round protection.
- ❖ Heel stiffener to reinforce the heel seat.
- ❖ **J-ESCAPE™ VIBRAM CA/PU** Walking Sole equipped with a shock absorber protecting the back and joints from vibrations and the **JAL'GRIP SYSTEM**, double standard LG marking in accordance with **EN ISO 20345:2021**, allows attachment to the ladders and prevents the risk of falling from a height.

Slip resistance tests results EN Standard ISO 20345:2022

Test ground : Ceramic / NaLS (Sodium lauryl sulfate)

A- Heel to the front **0,39** (>0,31)
B- Front to back **0,43** (>0,36)

Additional requirement **SR** : Ceramic /Glycerin

C - Heel to the front **0,29** (>0,19)
D- Front to back **0,29** (>0,22)

- ◆ Comfort layer in **Softane™** Densité = 0,45. Ensures comfort while walking and helps absorb vibrations.
- ◆ **Néotril™** ground contact layer equipped with **VIBRAM®** system :
 - ▶ Very good resistance to contact heat (300°C).
 - ▶ High abrasion resistance.
 - ▶ Heel shock absorption > 20 Joules.
 - ▶ Self-cleaning deep structure cleats (6,5 mm).

Weight	Gross weight (42) : 1828 g / Net weight (42) : 1610 g			
Size	35 to 39	40 to 42	43 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	335 x 210 x 130		335 x 244 x 130	365 x 260 x 133
Cartons (mm)	680 x 234 x 356	685 x 440 x 356	680 x 514 x 356	695 x 276 x 385



www.jallatte.com