

# JALMAYON SAS

## JJE24

**S3 HRO SRC**  
**EN ISO 20345:2011**  
**39 to 47**



- **Water-repellent full grain leather**
- **Vibram® J-ESCAPE sole**
- **Anti-static**

- ❖ Heavy duty boot with fast opening system. Black colour. Specific model for works in contact of molten metallic particles. Stitching realized with fireproofed thread Kevlar.
- ❖ Water-repellent full grain leather Thickness 1,9/2,1 mm. Lined sparks protection.
- ❖ Protective leather scuff cap over the toes to reinforce the boot and prolong its life under hostile working conditions.
- ❖ Breathable upper lining in 3D mesh, with honeycomb structure for improved all-round ventilation of the foot and fast-drying.
- ❖ Vamp lining in non-woven fabric. Resists scuffing and acid perspiration.
- ❖ Padded ergonomic collar in compact flexible foam, lined for extra comfort and better ankle and Achilles tendon protection.
- ❖ Heel stiffener to reinforce the heel seat.
- ❖ Inlay covering the entire surface of the foot, removable, antistatic, treated against bacteria, containing active carbon, anatomical and with heel cushioning. High capacity for absorbing and evaporating perspiration.
- ❖ **200 joules** steel toe-cap.
- ❖ Anti-static lasting sole.
- ❖ Steel midsole.
- ❖ **J-ESCAPE™ VIBRAM** outsole fitted with **progressive effect shock-absorber** to protect the back and joints from vibrations :

Slip resistance tests results	
EN Standard : EN ISO 20345 : 2011	
Requirement <b>SRC</b> (SRA+SRB)	
SRA Test ground : ceramic / lubricant : water and detergent	
On flat <b>0,40</b> (>0,32) – On the heel <b>0,39</b> (>0,28)	
SRB Test ground steel / lubricant : glycerine	
On flat <b>0,19</b> (>0,18) – On the heel: <b>0,16</b> (>0,13)	

- ◆ **Softane™** comfort layer
- ◆ Density = 0.45. Ensures comfortable walking for the wearer. Helps to absorb vibrations (40 Joules) and provided heat insulation to the sole of the foot.
- ◆ Ground contact layer in **Néotril™** :
- ◆ Very highly resistant to oils, greases and conducted heat (300°C)
- ◆ Highly scuff- resistant.
- ◆ Sole very resistant to hydrocarbons.



Weight	Gross weight (42) : 1674 g / Net weight (42) : 1456 g			
Size	39	40	41 to 45	46 to 47
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	340 x 210 x 133		340 x 245 x 133	
Cartons (mm)	685 x 225 x 359	685 x 440 x 359	685 x 505 x 359	685 x 255 x 359