

SOFTANE™ BTP



JALOAK SAS JJE40



S3 CI SRC
EN ISO 20345:2011
38 to 47

- **Water-repellent full-grain leather**
- **Dual density Softane™ sole**
- **Polymère toe cap / Antiperforation rustproof steel**
- **Antistatic**

- ❖ Safety shoe, derby type style outdoor, **adapted to the building sector**. Brown and black color.
- ❖ Water-repellent full-grain leather upper, pull-up finish, thickness 1,8 / 2,0 mm. Protective scuff cap reinforcement to vamp and heel for strength and long life in very demanding conditions: improved resistance to impacts, cuts and abrasion. Pu reinforcement to the front of the sole.
- ❖ Padded collar with compact flexible foam for extra comfort and better ankle and Achilles tendon protection.
- ❖ Fastened by 4 pairs of lace stays. Laces 90 cm.
- ❖ Padded, "3D' lined leather tongue to protect the top of the foot, with side bellows to keep out dust and dirt.
- ❖ Upper lined in breathable 3D mesh with honeycomb structure to improve the peripheral ventilation of the foot, dries out rapidly.
- ❖ Vamp lined in non-woven fabric. Resists scuffing and acid perspiration.
- ❖ **POLYJAL** footbed single-block structure made of soft polyurethane and textile, anatomical, perforated in the front part and with heel shock absorbers.
- ❖ Heel stiffener to reinforce the heel seat.
- ❖ Ergonomic shoe, with broad synthetic polymer toe cap **SPRINGTANE** , for saving on weight (50% lighter than steel). Impact resistance to 200 Joules.
- ❖ **Stainless rustproof steel midsole**.
- ❖ Dual density **Softane™ PU** sole, **robust and versatile**, with progressive shock absorber and anti-twist heel reinforcement integrated. Pu reinforcement to the front of the sole.

Slip resistance tests results

EN Standard : EN ISO 20345 : 2011

Requirement SRC (SRA+SRB)

SRA Test ground : ceramic / lubricant : water and detergent

On flat **0,73** (>0,32) – On the heel **0,70** (>0,28)

SRB Test ground steel / lubricant : glycerine

On flat **0,30** (>0,18) – On the heel: **0,28** (>0,13)

- Softane™ comfort layer, density 0.45 / Outsole density = 1.10.
- High abrasion resistance .
- Highly resistant to oils and hydrocarbons.
- Heel shock absorption > 20 Joules.
- Rugged sole pattern with self-cleaning treads, depth 6,5 mm.
- Very flat sole with a large contact area with the ground. Improved stability.

Weight	Gross weight (42) : 1430 g / Net weight (42) : 1222 g			
Size	38 to 39	40	41 to 45	46 to 47
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	306 x 192 x 114		340 x 210 x 133	
Cartons (mm)	590 x 210 x 320	590 x 410 x 320	685 x 440 x 359	685 x 225 x 359



www.jallatte.com