

# JALORKA SAS 00JJE58

# J-ESCAPE

S3 AN CI HI HRO SRC  
EN ISO 20345:2011  
38 to 47



- Water-repellent full-grain leather
- Sole Vibram® J-ESCAPE
- Polymère toe cap type B / Antiperforation rustproof steel
- Antistatic

- Original design of high-sided safety shoe. Brown and black color.
- Water-repellent full-grain leather upper, pull-up finish, thickness 1,8 / 2,0 mm. **Excellent impermeability**, no water crossing after 7h test. Very good breathability (evacuation of sweating well above normative requirements).
- Protective scuff cap reinforcement to vamp and heel for strength and long life in very demanding conditions: improved resistance to impacts, cuts and abrasion. Pu reinforcement to the front of the sole.
- Ankle protector system** on each side of the shoe. Inside result 5,9 kN, outside result 5,9 kN (EN standard requires an average of two values <10 kN).
- Upper lined in breathable **3D Surf** mesh with honeycomb structure to improve the peripheral ventilation of the foot, dries out rapidly.
- Padded collar with compact flexible foam for extra comfort and better ankle and Achilles tendon protection.
- Fastened by 4 pairs of lace stays and 2 pairs of open hooks. Laces 150 cm.
- Padded and lined leather tongue for instep protection with side bellows to keep out dust and dirt.
- Soft** footbed made of **BASF Dynamic polyurethane** with heat sensitive memory foam and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical, breathable
- This is a **DGUV 112-191** certified model, with the option of swapping the hygienic insole provided for a **SECOSOL®** orthopaedic insole.
- Ergonomic shoe with **broad synthetic polymer toe cap type B**, for saving on weight (50% lighter than steel) Impact resistance to **200 Joules**. Minimum height after test ≥ 4mm in relation to the Type A toe cap in accordance with Standard 22568-2:2021.
- Heel stiffener to reinforce the heel seat.
- Stainless rustproof steel midsole**.
- Sole J-ESCAPE™ VIBRAM CA/PU** with **progressive effect shock-absorber** to protect the back and joints from vibrations . Pu reinforcement to the front of the sole.



### Slip resistance tests results

EN Standard : EN ISO 20345 : 2011  
**Requirement SRC (SRA+SRB)**

**SRA** Test ground : ceramic / lubricant : water and detergent  
On flat **0,40** (>0,32) – On the heel **0,31** (>0,28)

**SRB** Test ground steel / lubricant : glycerine  
On flat **0,29** (>0,18) – On the heel: **0,21** (>0,13)

- Softane™** comfort layer
- Density = 0.45. Ensures comfortable walking for the wearer. Helps to absorb vibrations and provided heat insulation to the sole of the foot.
- Ground contact layer in **Néotril™** :
- Very highly resistant to oils, greases and conducted heat (300°C)
- Highly scuff- resistant.
- Sole very resistant to hydrocarbons.

Weight	Gross weight (42) : 1718 g / Net weight (42) : 1512 g			
Size	38 to 39	40	41 to 45	46 to 47
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	340 x 210 x 133		340 x 245 x 133	
Cartons (mm)	685 x 225 x 359	685 x 440 x 359	685 x 505 x 359	685 x 255 x 359

