

JALDARK SAS

00JJE64



S3 CI HI HRO SRC
EN ISO 20345:2011
38 to 47



- Water-repellent full-grain leather
- Sole Vibram® J-ESCAPE
- Antistatic and no magnétic
- Polymer toe cap type B and midsole no metallic

- ❖ Ankle boots with minimal stitching for increased watertightness. Black color.
- ❖ Water-repellent full-grain leather upper. Thickness 1.9/2.1mm
- ❖ Pu reinforcement to the front of the sole for more protection.
- ❖ Upper lined in breathable **3D Surf** mesh with honeycomb structure to improve the peripheral ventilation of the foot, dries out rapidly.
- ❖ Padded collar with compact flexible foam for extra comfort and better ankle and Achilles tendon protection.
- ❖ Padded and lined leather tongue for instep protection with side bellows to keep out dust and dirt.
- ❖ Fastened by 4 pairs of lace stays and 2 pairs of **Quick Lio (keeps the lace in place and allows for quick lacing and unlacing)**. Laces 130 cm.
- ❖ **Soft** footbed made of **BASF Dynamic polyurethane** with heat sensitive memory foam and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical, breathable
- ❖ Ergonomic shoe with **broad synthetic polymer toe cap type B**, for saving on weight (50% lighter than steel) Impact resistance to **200 Joules**. Minimum height after test ≥ 4 mm in relation to the Type A toe cap in accordance with Standard 22568-2 : 2021.
- ❖ Stab-resistant structural insole and liner in **FlexTane™ By Jallatte ESD**, in compliance with standard **22568-4 : 2021**, antistatic, **100% composite**. Sewn directly onto the upper and covering **100% of the foot for total protection**.
- ❖ Heel stiffener to reinforce the heel seat.
- ❖ **Sole J-ESCAPE™ VIBRAM CA/PU** with **progressive effect shock-absorber** to protect the back and joints from vibrations . Pu reinforcement to the front of the sole.



Slip resistance tests results

EN Standard : EN ISO 20345 : 2011

Requirement **SRC** (SRA+SRB)

SRA Test ground : ceramic / lubricant : water and detergent

On flat **0,40** (>0,32) – On the heel **0,31** (>0,28)

SRB Test ground steel / lubricant : glycerine

On flat **0,29** (>0,18) – On the heel: **0,21** (>0,13)

- **Softane™** comfort layer
- Density = 0.45. Ensures comfortable walking for the wearer. Helps to absorb vibrations and provided heat insulation to the sole of the foot.
- Ground contact layer in **Néotril™** :
- Very highly resistant to oils, greases and conducted heat (300°C)
- Highly scuff- resistant.
- Sole very resistant to hydrocarbons.

| | | | | |
|----------------|---|-----------------|-----------------|-----------------|
| Weight | Gross weight (42) : 1670 g / Net weight (42) : 1452 g | | | |
| Size | 38 to 39 | 40 | 41 to 45 | 46 to 47 |
| Packaging | 5 pairs | 10 pairs | | 5 pairs |
| Box shoes (mm) | 340 x 210 x 133 | | 340 x 245 x 133 | |
| Cartons (mm) | 685 x 225 x 359 | 685 x 440 x 359 | 685 x 505 x 359 | 685 x 255 x 359 |



www.jallatte.com